

CODE TABLES AND FLAG TABLES ASSOCIATED WITH BUFR TABLE B

Notes: In developing code tables associated with BUFR Table B to specify units of elements, the following principles should be applied:

- (a) Code tables specifying the units for an element which is defined, in the Manual on Codes, by a single symbolic letter shall be compatible with the relevant existing WMO code tables;
- (b) Code tables combining two or more existing WMO code tables to specify the units for an element which is defined, in the Manual on Codes, by a group of symbolic letters shall be compatible with the combined code figures of the relevant group of symbolic letters;
- (c) Code tables combining two or more existing WMO code tables to specify the units for an element which is defined, in the Manual on Codes, by different symbolic letters shall be compatible with the code figures of the relevant symbolic letters, with successive tens or hundreds values added, as appropriate;
- (d) Code tables and flag tables should only be used for reporting qualitative information. Quantitative information should be reported as observed using entries in Table 13. "Data description operators" from Table C should be applied when a "scale change" or "data width change" is required;
- (e) Reference to existing specification(s) and code table(s) in the Manual on Codes, with explanation of possible deviations, shall be given in an additional table annexed to the code tables associated with BUFR Table B.

0 01 003

WMO Region number/geographical area

Code
figure

0	Antarctica
1	Region I
2	Region II
3	Region III
4	Region IV
5	Region V
6	Region VI
7	Missing value

0 01 007

Satellite identifier

(See common Code table C-5 Part C/c.)

0 01 031

Identification of originating/generating centre

(See common Code table C-1 in Part C/c.)

0 01 33

Identification of originating/generating centre

(See common Code table C-1 in Part C/c.)

0 01 34

Identification of originating/generating sub-centre

(To be defined by centres themselves)
(See common Code table C-1 in Part C/c.)

0 01 036

Agency in charge of operating the observing platform

(the first 3 digits represent the ISO country code)

Code figure	
0-036000	Reserved
036001	Australia, Bureau of Meteorology (BOM)
036002	Australia, Joint Australian Facility for Ocean Observing Systems (JAFOOS)
036003	Australia, the Commonwealth Scientific and Industrial Research Organisation (CSIRO)
036004-124000	Reserved
124001	Canada, Marine Environmental Data Service (MEDS)
124002	Canada, Institute of Ocean Sciences (IOS)
124003-156000	Reserved
156001	China, The State Oceanic Administration
156002	China, Second Institute of Oceanography State Oceanic Administration
156003	China, Institute of Ocean Technology
156004-250000	Reserved
250001	France, Institut de Recherche pour le Développement (IRD)
250002	France, Institut Français de Recherche pour l'Exploitation de la mer (IFREMER)
250003-276000	Reserved
276001	Germany, Bundesamt fuer Seeschifffahrt und Hydrographie (BSH)
276002	Germany, Institut fuer Meereskunde, Kiel
276003-356000	Reserved
356001	India, National Institute of Oceanography (NIO)
356002	India, National Institute for Ocean Technology (NIOT)
356003	India, National Centre for Ocean Information Service
356004-392000	Reserved
392001	Japan, Japan Meteorological Agency (JMA)
392002	Japan, Frontier Observational Research System for Global Change
392003	Japan, Japan Marine Science and Technology Centre (JAMSTEC)
392004-410000	Reserved
410001	Korea Rep., Seoul National University
410002	Korea Rep., Korea Ocean Research and Development Institute (KORDI)
410003	Korea Rep., Meteorological Research Institute
410004-540000	Reserved
540001	New Caledonia, Institut de Recherche pour le Développement (IRD)
540002-554000	Reserved
554001	New Zealand, National Institute of Water and Atmospheric Research (NIWA)
554002-64300	Reserved
643001	Russia, State Oceanographic Institute of Roshydromet
643002	Russia, Federal Service for Hydrometeorology and Environmental Monitoring
643003-724000	Reserved
724001	Spain, Instituto Español de Oceanografía
724002-826000	Reserved
826001	United Kingdom, Hydrographic Office
826002	United Kingdom, Southampton Oceanography Centre (SOC)
826003-840000	Reserved
840001	USA, NOAA Atlantic Oceanographic and Meteorological Laboratories (AOML)
840002	USA, NOAA Pacific Marine Environmental Laboratories (PMEL)
840003	USA, Scripps Institution of Oceanography (SIO)
840004	USA, Woods Hole Oceanographic Institution (WHOI)
840005	USA, University of Washington
840006	USA, Naval Oceanographic Office

840007-1048574	Reserved
1048575	Missing value

0 02 01

Type of station

Code
figure

- | | |
|---|----------------------------------|
| 0 | Automatic station |
| 1 | Manned station |
| 2 | Hybrid:Both Manned and Automatic |
| 3 | Missing value |

0 02 002

Type of instrumentation for wind measurement

- | | |
|--------|---|
| Bit No | Type of Instrumentation and original units for wind measurement
(measured in m s^{-1} unless otherwise indicated) |
| 0 | |
| 1 | Certified Instruments |
| 2 | Originally measured in knots |
| 3 | Originally measured in kmh^{-1} |
| All 4 | Missing value |

0 02 003

Type of measuring equipment used

Code
figure

- | | |
|-------|---|
| 0 | Pressure Instrument associated with wind measuring equipment |
| 1 | Optical theodolite |
| 2 | Radio theodolite |
| 3 | Radar |
| 4 | VLF-Omega |
| 5 | Loran-C |
| 6 | Wind profiler |
| 7 | Satellite navigation |
| 8 | Radio-Acoustic Sounding System (RASS) |
| 9 | Sodar |
| 10-13 | Reserved |
| 14 | Pressure instrument associated with wind measuring equipment but pressure
element failed during ascent |
| 15 | Missing value |

0 02 004

Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported

Code figure	Instrumentation or crop type	Type of data
0	USA open pan evaporimeter (without cover)	} Evaporation
1	USA open pan evaporimeter (mesh covered)	
2	GGI-3000 evaporimeter (sunken)	
3	20 m ² tank	
4	Others	} Evapotranspiration
5	Rice	
6	Wheat	
7	Maize	
8	Sorghum	
9	Other crops	
10-14	Reserved	
15	Missing value	

0 02 011

Radiosonde type

(See common code table C-2 in part C/c.)

0 02 012

Radiosonde computational method

(To be developed)

0 02 013

Solar and Infrared radiation correction

Code figure	
0	No correction
1	CIMO solar corrected and CIMO infrared corrected
2	CIMO solar corrected and infrared corrected
3	CIMO solar corrected only
4	Solar and infrared corrected automatically by radiosonde system
5	Solar corrected automatically by radiosonde system
6	Solar and Infrared corrected as specified by country
7	Solar corrected as specified by country
8-14	Reserved
15	Missing value

0 02 014

Tracking technique/status of system used

(See common Code table C-7 in Part C/c.)

0 02 015

Radiosonde completeness

Code figure	
0	Reserved
1	Pressure only radiosonde
2	Pressure only radiosonde plus transponder
3	Pressure only radiosonde plus radar reflector
4	No-pressure radiosonde plus transponder
5	No-pressure radiosonde plus radar reflector
6-14	Reserved
15	Missing value

0 02 019

Satellite instruments

(See common Code table C-8 in Part C/c.)

0 02 020

Satellite classification

Code figure	
0	Nimbus
1	VTPR
2	Tiros 1 (Tiros, NOAA-6 to NOAA-13)
3	Tiros 2 (NOAA-14 onwards)
31	DMSP
61	EUMETSAT Polar System (EPS)
91	ERS
121	ADEOS
241	GOES
271	GMS
301	INSAT
331	METEOSAT Operational Programme (MOP)
332	METEOSAT Transitional Programme (MTP)
333	METEOSAT Second Generation Programme (MSG)
351	GOMS
381	FY-2
382-510	Reserved
511	Missing value

0 02 021

Satellite Instrument data used In processing

Bit No

1	High-resolution Infrared sounder (HIRS)
2	Microwave sounding unit (MSU)
3	Stratospheric sounding unit (SSU)
4	AMI (Advanced microwave instrument) Wind mode
5	AMI (Advanced microwave instrument) Wave mode
6	AMI (Advanced microwave instrument) Image mode
7	RADAR altimeter
8	ATSR (Along Track Scanning Radiometer)
All 9	Missing value

0 02 022

Satellite data-processing technique used

Bit flags denoting the elements Included in processing sounding data.

Bit No.

1	Processing technique not defined
2	Automated statistical regression
3	Clear path
4	Partly cloudy path
5	Cloudy path
6-7	Reserved
All 8	Missing value

Notes:

- (1) Clear path means the sounding has been generated from clear radiances derived from actual clear spot measurements. Tropospheric and stratospheric HIRS data, as well as MSU and SSU data, have been used.
- (2) Partly cloudy path means the sounding has been generated from clear radiances which have been calculated from partly cloudy spots. Tropospheric and stratospheric HIRS data, as well as MSU and SSU data, have been used.
- (3) Cloudy path means the sounding has been generated only from stratospheric HIRS data, MSU data and SSU data. Tropospheric HIRS data have not been used because of cloudy conditions.

0 02 023

Satellite Derived Wind Computation Method

Code	
Figure	
0	Reserved
1	Wind derived from cloud motion observed in the infrared channel
2	Wind derived from cloud motion observed in the visible channel
3	Wind derived from motion observed in the water vapour channel
4	Wind derived from motion observed in a combination of spectral channels
5	Wind derived from motion observed in the water vapour channel in clear air
6	Wind derived from motion observed in the ozone channel
7	Wind derived from motion observed in water vapour channel (cloud or clear air not specified)
8-14	Reserved
15	Missing value

0 02 024

Integrated mean humidity computational method

Code	
figure	
0	Reserved
1	Table with full range of humidity variation in layer
2	Regression technique on 2 humidity values in layer
3-14	Reserved
15	Missing value

0 02 025

Satellite channel(s) used in computation

Bit flags denoting the Instrument and/or channels used in obtaining various physical parameters. If, in any grouping of parameters, all bits = 0, then no retrieval was made for that parameter or set of parameters.

Bit No	Instrument (channels)	
1	Reserved	
	<i>Group 1 -</i>	Layer precipitable water for the layers: surface to 700 hPa, 700 to 500 hPa, and 500 to 300 hPa
2	HIRS	
3	MSU	
4-5	Reserved	
	<i>Group 2 -</i>	Tropopause temperature and pressure
6	HIRS	
7	MSU	
8-9	Reserved	
	<i>Group 3 - Total ozone</i>	
10	HIRS (1,2,3,8,9,16,17)	
11	HIRS (1, 2, 3, 9, 17)	
12	MSU	
13-14	Reserved	
	<i>Group 4 -</i>	Mean temperature for the layers: surface to 850 hPa, 850 to 700 hPa, 700 to 500 hPa, 500 to 400 hPa, 400 to 300 hPa, 300 to 200 hPa, and 200 to 100 hPa
15	HIRS	
16	HIRS*	
17	MSU	
18	SKINTK (ocean only)	
19-20	Reserved	
	<i>Group 5 -</i>	Channel combinations used to obtain mean temperatures for the layers 100 to 70 hPa, 70 to 50 hPa, 50 to 30 hPa, 30 to 10 hPa, 10 to 5 hPa, 5 to 2 hPa, 2 to 1 hPa, 1 to 0.4 hPa
21	HIRS*	
22	SSU	
23	MSU (3,4)	
24	Reserved	
All 25	Missing value	

Note: HIRS* is equivalent to: HIRS channel: 1 (669 cm⁻¹)
 2 (679cm⁻¹)
 3 (690cm⁻¹)
 4 (2358cm⁻¹)

0 02 030

Method of current measurement

Code	
Figure	
0	Reserved
1	ADCP (Acoustic Doppler Current Profiler)
2	GEK (Geomagnetic ElectroKinetograph)
3	Ship's set and drift determined by fixes 3-6 hours apart
4	Ship's set and drift determined by fixes more than 6 hours but less than 12 hours apart
5	Drift of buoy
6	Reserved
7	Missing value

0 02 031

Duration and Time of current measurement

Code Figure			
0	Reserved		
1	Instantaneous		
2	Averaged over 3 minutes or less	}	
3	Averaged over more than 3 minutes, but 6 at the most		between H-1 and H
4	Averaged over more than 6 minutes, but 12 at the most	}	
5	Instantaneous		between H-2 and H-1
6	Averaged over 3 minutes or less		
7	Averaged over more than 3 minutes, but 6 at the most		
8	Averaged over more than 6 minutes, but 12 at the most		
9	Vector or Doppler current profiling method not used		
10	Reserved		
11	1 hour or less		
12	More than 1 hour but 2 at the most		
13	More than 2 hours but 4 at the most		
14	More than 4 hours but 8 at the most		
15	More than 8 hours but 12 at the most		
16	More than 12 hours but 18 at the most		
17	More than 18 hours but 24 at the most		
18	Reserved		
19	Drift method not used		
20-30	Reserved		
31	Missing value		

Notes:

- (1) Code figures 1-9: Duration and time of current measurement (vector or Doppler current profiling method).
- (2) Code figures 11-19: Period of current measurement (drift method).
- (3) H = Time of observation.

0 02 032

Indicator for digitization

Code figure	
0	Values at selected depths (data points fixed by the instrument or selected by any other method)
1	Values at selected depths (data points taken from traces at significant depths)
2	Reserved
3	Missing value

0 02 033

Method of salinity/depth measurement

Code	
Figure	
0	No salinity measured
1	<i>In situ</i> sensor, accuracy better than 0.02 ‰
2	<i>In situ</i> sensor, accuracy less than 0.02 ‰
3	Sample analysis
4-6	Reserved
7	Missing value

0 02 034

Drogue type

Code	
Figure	
0	Unspecified drogue
1	Holey sock
2	TRISTAR
3	Window shade
4	Parachute
5	Non-Lagrangian sea anchor
6-30	Reserved (to be developed)
31	Missing value

0 02 036

Buoy type

Code	
Figure	
0	Drifting buoy
1	Fixed buoy
2	Sub-surface float (moving)
3	Missing value

0 02 037

Method of tidal observation

Code Figure	
0	Reserved
1	Manual reading from vertical tide staff
2	Manual reading from single automatic recorder at station
3	Manual reading from multiple automatic recorders at station
4	Automatic reading from single automatic recorder at station without level reference check.
5	Automatic reading from a single automatic recorder at station with level reference check, or from multiple automatic recorders.
6	Reserved
7	Missing value

0 02 038

Method of sea surface temperature measurement

Code Figure	
0	Ship intake
1	Bucket
2	Hull contact sensor
3	Reversing Thermometer
4	STD/CTD sensor
5	Mechanical BT
6	Expendable BT
7	Digital BT
8	Thermistor chain
9	Infra-red scanner
10	Micro-wave scanner
11-14	Reserved
15	Missing value

0 02 039

Method of wet bulb temperature measurement

Code Figure	
0	Measured wet-bulb temperature
1	Iced bulb measured wet-bulb temperature
2	Computed wet-bulb temperature
3	Iced bulb computed wet-bulb temperature
4-6	Reserved
7	Missing value

0 02 040

Method of removing code velocity and motion of platform from current

Code			
Figure			
0	Ships motion removed by averaging	}	Ship's velocity removed by botton tracking
1	Ships motion removed by motion compensation		
2	Ships motion not removed	}	Ship's velocity removed by navigation
3	Ships motion removed by averaging		
4	Ships motion removed by motion compensation		
5	Ships motion not removed		
6	Doppler current profiling method not used		
7-14	Reserved		
15	Missing value		

0 02 041

Method for estimating reports related to synoptic features

Code	
figure	
0	Information based on manual analysis
1	Information based on computer analysis
2	Information based on data assimilation
3	Information based on computer analysis or data assimilation manually modified
4-9	Reserved
10	Information based on the numerical weather prediction
11-62	Reserved for future use
63	Missing value

0 02 044

Indicator for method of calculation of spectral wave data

Code	
Figure	
0	Reserved for future use
1	Longuet-Higgins (1964)
2	Longuet-Higgins (F3 method)
3	Maximum likelihood method
4	Maximum entropy method
5-14	Reserved
15	Missing value

0 02 045

Indicator for type of platform

Code Figure	
0	Sea station
1	Automatic data buoy
2	Aircraft
3	Satellite
4-14	Reserved
15	Missing value

0 02 046

Wave measurement instrumentation

Code Figure	
0	Reserved for future use
1	Heave sensor
2	Slope sensor
3-14	Reserved
15	Missing value

0 02 048

Satellite sensor indicator

Code Figure	
0	HIRS
1	MSU
2	SSU
3	AMSU-A
4	AMSU-B
5	AVHRR
6	SSMI
7	NSCAT
8	SEAWINDS
9-14	Reserved
15	Missing value

0 02 049

Geostationary satellite data-processing technique used

Bit No.	
1	Processing technique not defined
2	Simultaneous physical retrieval
3	Clear sounding
4	Cloudy sounding
5-7	Reserved for future use
All 8	Missing value

Notes:

1. Clear sounding indicates the sounding has been generated from a set of clear radiances using all available sounder radiances.
2. Cloudy sounding indicates that sufficient clear radiances could not be identified in the sounding area. The sounding is calculated from the cloud top (cloud pressure greater than or equal to 70 hPa) upwards.

0 02 050

Geostationary sounder satellite channels used

Bit No.	Channel	Central wavelength (micrometers)
1	1	14.71
2	2	14.37
3	3	14.06
4	4	13.64
5	5	13.37
6	6	12.66
7	7	12.02
8	8	11.03
9	9	9.71
10	10	7.43
11	11	7.02
12	12	6.51
13	13	4.57
14	14	4.52
15	15	4.45
16	16	4.13
17	17	3.98
18	18	3.74
19	19	0.969
All 20	Missing value	

Note: Beginning with the first bit position (high order bit), if the bit position is set to one, then the channel is used. If the bit position is set to zero, then the channel is not used.

0 02 051

Indicator to specify observing method for extreme temperatures

Code figure	
0	Reserved
1	Maximum/minimum temperatures
2	Automated instruments
3	Thermograph
4-14	Reserved
15	Missing value

0 02 052

Geostationary imager satellite channels used

Bit No.	Channel	Central wavelength (micrometer)
1	1	0.55 - 0.75
2	2	3.9
3	3	6.7
4	4	10.7
5	5	12.0
All 6	Missing value	

Note: Beginning with the first bit position (high order bit), if the bit position is set to one, then the channel is used. If the bit position is set to zero, then the channel is not used.

0 02 053

GOES-I/M brightness temperature characteristics

Code figure	
0	Observed brightness temperature
1	Brightness temperature with bias correction applied
2	Brightness temperature calculated from first guess
3	Brightness temperature calculated from sounding
4-14	Reserved
15	Missing value

0 02 054

IGOES-I/M soundings parameter characteristics

Code figure	
0	Parameter derived using observed sounder brightness temperatures
1	Parameter derived using observed imager brightness temperatures
2	Parameter derived using first guess information
3	Parameter derived NMC analysis information
4	Parameter derived using radiosonde information
5-14	Reserved
15	Missing value

0 02 055

Geostationary soundings statistical parameters

Code figure	
0	Statistics generated comparing retrieval versus radiosonde
1	Statistics generated comparing retrieval versus first guess
2	Statistics generated comparing radiosonde versus first guess
3	Statistics generated comparing observed versus retrieval
4	Statistics generated comparing observed versus first guess
5	Statistics generated comparing radiosonde versus imager
6	Statistics generated comparing radiosonde versus sounder
7	Statistics generated for radiosonde
8	Statistics generated for first guess
9-14	Reserved
15	Missing value

0 02 056

Geostationary soundings accuracy statistics

Code figure	
0	Sums of differences
1	Sums of squared differences
2	Simple size
3	Minimum difference
4	Maximum difference
5-14	Reserved
15	Missing value

0 02 057

Origin of first guess information for GOES-I/M soundings

Code figure	
0	Nested Grid Model (NGM)
1	Aviation Model (AVN)
2	Medium Range Forecast (MRF) Model
3	Global Data Assimilation System (GDAS) Forecast Model
4	Prior soundings (within 3 hours of current time)
5	Climatology
6-14	Reserved
15	Missing value

0 02 058

Valid times of first guess information of GOES-I/M soundings

Code
figure

0	12 hour and 18 hour
1	18 hour and 24 hour
2	6 hour and 12 hour
3	Greater than 24 hours
4-14	Reserved
15	Missing value

0 02 059

Origin of analysis information for GOES-I/M soundings

Code
figure

0	NCEP Nested Grid Model (NGM) Analysis
1	NCEP Aviation Model (AVN) Analysis
2	NCEP Medium Range Forecast (MRF) Model Analysis
3	NCEP Global Data Assimilation System (GDAS) Forecast Model Analysis
4-14	Reserved
15	Missing value

0 02 060

Origin of surface information for GOES-I/M soundings

Code
figure

0	Current surface hourly reports
1	Current ship reports
2	Current buoy reports
3	One hour old surface hourly reports
4	One hour old ship reports
5	One hour old buoy reports
6-14	Reserved
15	Missing value

0 02 061

Aircraft navigational system

Code
figure

0	Inertial navigation system
1	OMEGA
2-6	Reserved
7	Missing value

0 02 062

Type of aircraft data relay system

Code figure	
0	ASDAR
1	ASDAR (ACARS also available but not operative)
2	ASDAR (ACARS also available and operative)
3	ACARS
4	ACARS (ASDAR also available but not operative)
5	ACARS (ASDAR also available and operative)
6-14	Reserved
15	Missing value

0 02 064

Aircraft roll angle angle quality

Code figure	Meaning
0	Good
1	Bad
2	Reserved
3	Missing value

Note: Bad is currently defined as a roll angle >5 degrees from vertical.

0 02 070

Original specification of latitude/longitude

Code figure	
0	Actual location in seconds
1	Actual location in minutes
2	Actual location in degrees
3	Actual location in decidegrees
4	Actual location in centidegrees
5	Referenced to checkpoint in seconds
6	Referenced to checkpoint in minutes
7	Referenced to checkpoint in degrees
8	Referenced to checkpoint in decidegrees
9	Referenced to checkpoint in centidegrees
10	Actual Location in tenths of a minute
11	Referenced to checkpoint in tenths of a minute
12-14	Reserved
15	Missing value

0 02 101

Type of antenna

Code figure	
0	Centre front-fed paraboloid
1	Offset front-fed paraboloid
2	Centre Cassegrain paraboloid
3	Offset Cassegrain paraboloid
4	Planar array
5	Coaxial-collinear array
6	Yagi elements array
7	Microstrip
8-13	Reserved
14	Other
15	Missing value

0 02 103

Radome

Bit No.	
1	Radar antenna is protected by a radome
All 2	Missing value

0 02 104

Antenna polarization

Code figure	
0	Horizontal polarization
1	Vertical polarization
2	Right circular polarization
3	Left circular polarization
4	Horizontal and vertical polarization
5	Right and left circular polarization
6-14	Reserved
15	Missing value

0 02 131

Sensitivity time control (STC)

Bit No.	
1	STC operational
All 2	Missing values

0 02 143

Ozone instrument type

Code	
Figure	
0	Reserved
1	Brewer spectrophotometer
2	Caver Teichert
3	Dobson
4	Dobson (Japan)
5	Ehmet
6	Fecker telescope
7	Hoelper
8	Jodmeter
9	Filter Ozonometer M-83
10	Mast
11	Oxford
12	Paetzold
13	Regener
14	Reserved for future use
15	Vassy filter Ozonometer
16	Carbon iodide
17	Surface ozone bubler
18	Filter Ozonometer M-124
19	ECC sonde
20-126	Reserved
127	Missing value

0 02 144

Light source type of Brewer spectrophotometer

Code	
figure	
0	Direct Sun
1	Direct Sun, attenuator #1
2	Direct Sun, attenuator #2
3	Focussed Moon
4	Focussed Sun
5	Focussed Sun corrected with adjacent sky measurements
6	Zenith Sky
7-14	Reserved
15	Missing value

Note: Entries 1 and 2 should not be used.

0 02 145

Wave length setting for Dobson instruments

Code figure	
0	Wavelengths AD ordinary setting
1	Wavelengths BD ordinary setting
2	Wavelengths CD ordinary setting
3	Wavelengths CC' ordinary setting
4	Wavelengths AD focussed image
5	Wavelengths BD focussed image
6	Wavelengths CD focussed image
7	Wavelengths CC' focussed image
8-14	Reserved
15	Missing value

0 02 146

Source condition for Dobson instruments

Code figure	
0	on direct sun
1	on direct moon
2	on blue zenith sky
3	on zenith cloud (uniform stratified layer of small opacity)
4	on zenith cloud(uniform or moderately variable layer of medium opacity)
5	on zenith cloud (uniform or moderately variable layer of large opacity)
6	on zenith cloud (highly variable opacity, with or without precipitation)
7	on zenith cloud (fog)
8	On zenith haze
9	On direct sun through thin cloud, fog or haze
10-14	reserved
15	Missing value

0.02 148

Data collection and/or location system

Code figure	
0	Reserved
1	Argos
2	GPS
3	GOES DCP
4	METEOSAT DCP
5-30	Reserved
31	Missing value

0 02 149

Type of data bouy

Code figure	
0	Unspecified drifting buoy
1	Standard Lagrangian drifter (Global Drifter Programme)
2	Standard FGGE type drifting buoy (non-Lagrangian meteorological drifting buoy)
3	Wind measuring FGGE type drifting buoy (non-Lagrangian meteorological drifting buoy)
4	Ice float
5-7	Reserved
8	Unspecified sub-surface float
9	SOFAR
10	ALACE
11	MARVOR
12	RAFOS
13-15	Reserved
16	Unspecified moored buoy
17	Nomad
18	3-metre discus
19	10-12-metre discus
20	ODAS 30 series
21	ATLAS (e.g. TAO area)
22	TRITON buoy
23	Reserved
24	Omnidirectional waverider
25	Directional waverider
26	Sub-surface ARGO float
27-62	Reserved
63	Missing value

0 02 150***TOVS/ATOVS/AVHRR instrumentation channel number***

code figure		Code figure	
0	Reserved	28	AMSU-A 1
1	HIRS 1	29	AMSU-A 2
2	HIRS 2	30	AMSU-A 3
3	HIRS 3	31	AMSU-A 4
4	HIRS 4	32	AMSU-A 5
5	HIRS 5	33	AMSU-A 6
6	HIRS 6	34	AMSU-A 7
7	HIRS 7	35	AMSU-A 8
8	HIRS 8	36	AMSU-A 9
9	HIRS 9	37	AMSU-A 10
10	HIRS 10	38	AMSU-A 11
11	HIRS 11	39	AMSU-A 12
12	HIRS 12	40	AMSU-A 13
13	HIRS 13	41	AMSU-A 14
14	HIRS 14	42	AMSU-A 15
15	HIRS 15	43	AMSU-B 1
16	HIRS 16	44	AMSU-B 2
17	HIRS 17	45	AMSU-B 3
18	HIRS 18	46	AMSU-B 4
19	HIRS 19	47	AMSU-B 5
20	HIRS 20	48	AVHRR 1
21	MSU 1	49	AVHRR 2
22	MSU 2	50	AVHRR 3a
23	MSU 3	51	AVHRR 3b
24	MSU 4	52	AVHRR 4
25	SSU 1	53	AVHRR 5
26	SSU 2	54-62	Reserved
27	SSU 3	63	Missing value

0 02 151***Radiometer identifier***

Code figure	
0	HIRS
1	MSU
2	SSU
3	AMSU-A1-1
4	AMSU-A1-2
5	AMSU-A2
6	AMSU-B
7	AVHRR
8-2046	Reserved
2047	Missing value

0 02 152

Satellite instrument data used in processing

Bit No.	
1	High-resolution infrared sounder(HIRS)
1	Microwave sounding unit (MSU)
3	Stratospheric sounding unit (SSU)
4	AMI wind mode
5	AMI wave mode
6	AMI image mode
7	RADAR altimeter
8	ATSR
9	Geostationary Imager
10	Geostationary Sounder
11	Geostationary Earth radiation (GERB)
12-30	Reserved
All 31	Missing value

0 02 163

Height assignment method

Code figure	
0	Reserved
1	IRW height assignment
2	WV height assignment
3	H2O intercept height assignment
4	CO2 slicing height assignment
5	Low pixel max gradient
6	Higher pixel max gradient
7	Primary height assignment
8	Layer thickness assignment
9	Cumulative contribution function -10 percent height
10	Cumulative contribution function -50 percent height
11	Cumulative contribution function -90 percent height
12	Cumulative contribution function - height of maximum gradient
13-14	Reserved
15	Missing value

0 02 164

Tracer correlation method

Code figure	
0	LP - Norms least square minimum
1	EN - Euclidean norm with radiance correlation
2	CC - Cross correlation
3-6	Reserved
7	Missing value

0 02 166

Radiance type

Code figure	
0	Type not defined
1	Automated statistical regression
2	Clear path
3	Partly cloudy path
4	Cloudy path
5-14	Reserved
15	Missing value

0 02 167

Radiance computational method

Code figure	
0	Method not defined
1	1b raw radiance
2	processed radiance
3-14	Reserved
15	Missing value

0 02 169

Anemometer type

Code figure	
0	Cup rotor
1	Propeller rotor
2	Wind Observation Through Ambient Noise (WOTAN)
3-14	Reserved
15	Missing value

0 02 172

Product type for retrieved atmospheric gases

Code figure	
0	Reserved
1	Retrieval from a nadir sounding
2	Retrieval from a limb sounding
3-254	Reserved
255	Missing value

0 08 001

Vertical sounding significance

Bit No.	
1	Surface
2	Standard level
3	Tropopause level
4	Maximum wind level
5	Significant level, temperature
6	Significant level, wind
All 7	Missing value

0 08 002

Vertical significance (surface observations)

Code figure	
0	Observing rules for base of lowest cloud and cloud types of FM 12SYNOP and FM 13 SHIP apply
1	First significant layer
2	Second significant layer
3	Third significant layer
4	Cumulonimbus layer
5	Ceiling
6	Clouds not detected below the following height(s)
7	Low cloud
8	Middle cloud
9	High cloud
10-62	Reserved
63	Missing value

0 08 003

Vertical significance (satellite observations)

Code figure	
0	Surface
1	Base of Satellite sounding
2	Cloud top
3	Tropopause
4	Precipitable water
5	Sounding Radiances
6	Mean Temperatures
7	Ozone
8-62	Reserved
63	Missing value

0 08 004

Phase of aircraft flight

Code
figure

0-1	Reserved
2	Unsteady (UNS)
3	Level flight, routine observation (LVR)
4	Level flight, highest wind encountered (LVW)
5	Ascending (ASC)
6	Descending (DES)
7	Missing value

0 08 005

Meteorological attribute significance

Code
figure

0	Reserved
1	Storm center
2	Outer limit or edge of storm
3	Location of maximum wind
4-14	Reserved
15	Missing value

0 08 006

Ozone vertical sounding significance

Bit No.

1	Surface
2	Standard level
3	Tropopause level
4	Prominent maximum level
5	Prominent minimum level
6	Minimum pressure level
7	Reserved
8	Level of undetermined significance
All 9	Missing value

0 08 007

Dimensional significance

Code figure	
0	Point
1	Line
2	Area
3	Volume
4-14	Reserved
15	Missing value

Note: A consecutive sequence of 2 or more of location coordinates, such as latitude and longitude pairs, defines a line or polygon. Points shall be joined in the order given in the message. Any area described will fall left of the drawn boundary in the direction established by the order of the points given in the message. This definition is for simple non-intersecting polygons without holes.

0 08 008

Radiation vertical sounding significance

Bit No.	
1	Surface
2	Standard level
3	Tropopause level
4	Level of beta radiation maximum
5	Level of gamma radiation maximum
6	Minimum pressure level
7	Reserved
8	Level of undetermined significance
All 9	Missing value

0 08 011

Meteorological Feature

Code
figure

0	Quasi-stationary front at the surface
1	Quasi-stationary front above the surface
2	Warm front at the surface
3	Warm front above the surface
4	Cold front at the surface
5	Cold front above the surface
6	Occlusion
7	Instability line
8	Intertropical front
9	Convergence line
10	Jet stream
11	Cloud clear
12	Cloud
13	Turbulence
14	Storm
15	Airframe icing
16	Phenomenon
17	Volcano
18	Atmospherics
19	Reserved
20	Special clouds
21-62	Reserved
63	Missing value

0 08 012

Land/sea qualifier

Code
figure

0	Land
1	Sea
2	Coastal
3	Missing value

0 08 013

Day/Night qualifier

Code
Figure

0	Night
1	Day
2	Reserved
3	Missing value

0 08 014

Qualifier for runway visual range

Code figures		
0	10-minute mean value	- normal value
1	10-minute mean value	- above the upper limit for assessments of RVR (P)
2	10-minute mean value	- below the lower limit for assessments of RVR (M)
3	one-minute minimum value	- normal value
4	one-minute minimum value	- above the upper limit for assessments of RVR (P)
5	one-minute minimum value	- below the lower limit for assessments of RVR (M)
6	one-minute maximum value	- normal value
7	one-minute maximum value	- above the upper limit for assessments of RVR (P)
8	one-minute maximum value	- below the lower limit for assessments of RVR (M)
9-14	Reserved	
15	Missing value	

0 08 016

Change qualifiers of a trend-type forecast or an aerodrome forecast

Code figures	
0	NOSIG
1	BECMG
2	TEMPO
3	FM
4-6	Reserved
7	Missing value

0 08 017

Qualifier of the time when the forecast change is expected

Code figures	
0	FM
1	TL
2	AT
3	Missing value

0 08 018

SEAWINDS land/ice surface type

Bit No.	
1	Land is present
2	Surface ice map indicates ice is present
3-10	Reserved
11	Ice map data not available
12	Attenuation map data not available
13-16	Reserved
All 17	Missing value

0 08 021

Time significance

Code figure	
0	Reserved
1	Time series
2	Time averaged
3	Accumulated
4	Forecast
5	Forecast time series
6	Forecast time averaged
7	Forecast accumulated
8	Ensemble mean
9	Ensemble mean time series
10	Ensemble mean time averaged
11	Ensemble mean accumulated
12	Ensemble mean forecast
13	Ensemble mean forecast time series
14	Ensemble mean forecast time averaged
15	Ensemble mean forecast accumulated
16	Analysis
17	Start of phenomenon
18	Radiosonde launch time
19	Start of orbit
20	End of orbit
21	Time of ascending node
22	Time of occurrence of wind shift
23	Monitoring period
24	Agreed time limit for report reception
25	Nominal reporting time
26	Time of last known position
27	First guess
28	Start of scan
29	End of scan
30	Reserved
31	Missing value

Notes:

- (1) "Time averaged" indicates that values are continuously averaged over a period of time.
- (2) "Ensemble mean" indicates that a number of distinct values corresponding to a set of time locations are averaged.
- (3) Time significance must be qualified by appropriate time periods being specified.

0 08 023

First Order Statistics

Code Figure	
0	Reserved
1	Reserved
2	Maximum value
3	Minimum value
4	Mean value
5	Median value
6	Modal value
7	Mean absolute error
8	Reserved
9	Best estimate of standard deviation (N-1)
10	Standard deviation (N)
11	Harmonic mean
12	Root-mean-square vector error
13-31	Reserved
32	Vector mean
33-62	Reserved for local use
63	Missing value

NOTE: All first order statistics are in the units defined by the original data descriptors.

0 08 024

Difference Statistics

Code Figure	
0	Reserved
1	Reserved
2	Observed minus maximum
3	Observed minus minimum
4	Observed minus mean
5	Observed minus median
6	Observed minus mode
7-10	Reserved
11	Observed minus climatology (anomaly)
12	Observed minus analyzed value
13	Observed minus initialized analysed value
14	Observed minus forecast value
15-20	Reserved
21	Observed minus interpolated value
22	Observed minus hydrostatically calculated value
23-31	Reserved
32-62	Reserved for local use
63	Missing value

Notes:

- (1) Difference statistics are difference values; they have dimensions the same as the corresponding reported values with respect to units, but assume a range centred on zero (e.g., the difference between reported and analysed values, the difference between reported and forecast values, etc.).
- (2) Where observed minus forecast values are represented, the period of the forecast shall be indicated by an appropriate descriptor from class 4.

0 08 025

Time difference qualifier

Code

Figure

0	Universal Time Coordinated (UTC) minus Local Standard Time (LST)
1	Local Standard Time
2	Universal Time Coordinated (UTC) minus Satellite clock
3-4	Reserved
5	Time difference from edge of processing segment
6-14	Reserved
15	Missing value

0 08 033

Method of derivation of percentage confidence

Code Figure	
0	Reserved
1	Percentage confidence calculated using cloud fraction
2	Percentage confidence calculated using standard deviation of temperature
3-126	Reserved
127	Missing value

0 08 035

Type of monitoring exercise

Code figure	
0	Global
1	Regional
2	National
3	Special
4	Bilateral
5	Reserved
6	Reserved
7	Missing value

0 08 036

Type of centre or station performing monitoring

Code figure	
0	WMO Secretariat
1	WMO
2	RSMC
3	NMC
4	RTH
5	Observing site
6	Other
7	Missing value

0 08 051

Qualifier for number of missing values in calculation of statistic

Code figure	
1	Pressure
2	Temperature
3	Extreme temperature
4	Vapour pressure
5	Precipitation
6	Sunshine duration
7	Missing value

0 08 052

Condition for which number of days of occurrence follows

Code
figure

0	Mean wind speed over a 10-minute period observed or recorded equal to or more than 10 m/s or 20 knots
1	Mean wind speed over a 10-minute period observed or recorded equal to or more than 20 m/s or 40 knots
2	Mean wind speed over a 10-minute period observed or recorded equal to or more than 30 m/s or 60 knots
3	Maximum temperature less than 273.2 K
4	Maximum temperature equal to or more than 298.2 K
5	Maximum temperature equal to or more than 303.2 K
6	Maximum temperature equal to or more than 308.2 K
7	Maximum temperature equal to or more than 313.2 K
8	Minimum temperature less than 273.2 K
9	Maximum temperature equal to or more than 273.2 K
10	Precipitation equal to or more than 1.0 kgm ⁻²
11	Precipitation equal to or more than 5.0 kgm ⁻²
12	Precipitation equal to or more than 10.0 kgm ⁻²
13	Precipitation equal to or more than 50.0 kgm ⁻²
14	Precipitation equal to or more than 100.0 kgm ⁻²
15	Precipitation equal to or more than 150.0 kgm ⁻²
16	Snow depth more than 0.00 m
17	Snow depth more than 0.01 m
18	Snow depth more than 0.10 m
19	Snow depth more than 0.50 m
20	Horizontal visibility less than 50 m
21	Horizontal visibility less than 100 m
22	Horizontal visibility less than 1000 m
23	Hail
24	Thunderstorm
25-30	Reserved
31	Missing value

0 08 053

Day of occurrence qualifier

Code
figure

0	Value occurred on only one day in the month
1	Value occurred on more than one day in the month
2	Reserved
3	Missing value

0 08 060

Sample Scanning Mode Significance

Code figure	
0	Reserved
1	Range
2	Azimuth
3	Horizontal
4	Vertical
5-14	Reserved
15	Missing value

0 08 070

TOVS/ATOVS product qualifier

Code figure	
0	Reserved
1	Reserved
2	Earth located instrument counts, calibration coefficients and housekeeping (level 1b)
3	Earth located calibrated radiances (level 1c)
4	Mapped to a common footprint, earth located calibrated radiances (level 1d)
5-14	Reserved
15	Missing value

0 08 072

Pixel(s) type

Code figure	
0	Mixed
1	Clear
2	Cloudy
3-6	Reserved
7	Missing value

0-08-075

Ascending/Descending Orbit Qualifier

Code figure	
0	Ascending orbit
1	Descending orbit
2	Reserved
3	Missing value

Characteristic of pressure tendencyCode
figure

0	Increasing, then decreasing; atmospheric pressure the same or higher than 3 hours ago
1	Increasing, then steady; or Increasing, then Increasing more slowly. Atmospheric pressure now higher than 3 hours ago.
2	Increasing (steadily or unsteadily) Atmospheric pressure now higher than 3 hours ago.
3	Decreasing or steady, then increasing; or increasing, then increasing more rapidly Atmospheric pressure now higher than 3 hours ago.
4	Steady; atmospheric pressure the same as 3 hours ago
5	Decreasing, then increasing; atmospheric pressure the same or lower than 3 hours ago
6	Decreasing, then steady; or decreasing, then decreasing more slowly. Atmospheric pressure now lower than 3 hours ago.
7	Decreasing (steadily or unsteadily). Atmospheric pressure now lower than 3 hours ago.
8	Steady or increasing, then decreasing; or decreasing, then decreasing more rapidly. Atmospheric pressure now lower than 3 hours ago.
9-14	Reserved
15	Missing value

Notes:

- (1) In reports from automatic stations, code figure 2 shall be used when tendency is positive, 7 when negative, and 4 when the pressure is the same as 3 hours before.
- (2) In reports from tropical stations reporting 24-hour pressure changes, code figure 2 shall be used when tendency is positive, 7 when negative, and 4 when pressure is the same as 24 hours before.

0 11 031

Degree of turbulence

Code figure		
0	Nil	} In cloud
1	Light	
2	Moderate	
3	Severe	} In clear air
4	Nil	
5	Light	
6	Moderate	} Cloud/clear air not specified
7	Severe	
8	Nil	
9	Light	
10	Moderate	
11	Severe	
12	Extreme, In clear air	
13	Extreme, In cloud	
14	Extreme, cloud/clear air not specified	
15	Missing value	

0 11 037

Turbulence index

Code figure	Average Value of Eddy Dissipation Rate (ave) ($m^{2/3} s^{-1}$)	Peak Value of Eddy Dissipation Rate (peak) ($m^{2/3} s^{-1}$)
0	ave <0.1	peak <0.1
1	ave <0.1	0.1 <= peak <0.2
2	0.1 <= ave <0.2	0.1 <= peak <0.2
3	ave <0.1	0.2 <= peak <0.3
4	0.1 <= ave <0.2	0.2 <= peak <0.3
5	0.2 <= ave <0.3	0.2 <= peak <0.3
6	ave <0.1	0.3 <= peak <0.4
7	0.1 <= ave <0.2	0.3 <= peak <0.4
8	0.2 <= ave <0.3	0.3 <= peak <0.4
9	0.3 <= ave <0.4	0.3 <= peak <0.4
10	ave <0.1	0.4 <= peak <0.5
11	0.1 <= ave <0.2	0.4 <= peak <0.5
12	0.2 <= ave <0.3	0.4 <= peak <0.5
13	0.3 <= ave <0.4	0.4 <= peak <0.5
14	0.4 <= ave <0.5	0.4 <= peak <0.5
15	ave <0.1	0.5 <= peak <0.8
16	0.1 <= ave <0.2	0.5 <= peak <0.8
17	0.2 <= ave <0.3	0.5 <= peak <0.8
18	0.3 <= ave <0.4	0.5 <= peak <0.8
19	0.4 <= ave <0.5	0.5 <= peak <0.8
20	0.5 <= ave <0.8	0.5 <= peak <0.8
21	ave <0.1	0.8 <= peak
22	0.1 <= ave <0.2	0.8 <= peak
23	0.2 <= ave <0.3	0.8 <= peak
24	0.3 <= ave <0.4	0.8 <= peak
25	0.4 <= ave <0.5	0.8 <= peak
26	0.5 <= ave <0.8	0.8 <= peak
27	0.8 <= ave	0.8 <= peak
28	Nil	Nil
29-62	Reserved	Reserved
63	Missing value	Missing value

0 11 038

Time of Occurrence of Peak Eddy Dissipation Rate

Code figure	Minutes prior to observation time (min)
0	min < 1
1	1 <= min < 2
2	2 <= min < 3
3	3 <= min < 4
4	4 <= min < 5
5	5 <= min < 6
6	6 <= min < 7
7	7 <= min < 8
8	8 <= min < 9
9	9 <= min < 10
10	10 <= min < 11
11	11 <= min < 12
12	12 <= min < 13
13	13 <= min < 14
14	14 <= min < 15
15	No timing information available
16-30	Reserved
31	Missing value

0 13 038

Superadiabatic indicator

Code
figure

0	Not superadiabatic
1	Superadiabatic
2	Reserved
3	Missing value

0 13 039

Terrain type (ice/snow)

Code
figure

0	Sea ice
1	Snow on land
2-6	Reserved
7	Missing value

0 13 041

Pasquill-Gifford stability category

Code
figure

1	A
2	A-B
3	B
4	B-C
5	C
6	D
7	E
8	F
9	G
10-14	Reserved
15	Missing value

0 13 051

Frequency group, precipitation

Code
figure

0	Smaller than any value in the 30-year period
1	In the first quintile
2	In the second quintile
3	In the third quintile
4	In the fourth quintile
5	In the fifth quintile
6	Greater than any value in the 30-year period
7-14	Reserved
15	Missing value

0 19 001

Type of synoptic feature

Code figure	
0	Depression or low (extratropical)
1	Tropical depression
2	Tropical storm
3	Severe tropical storm
4	Typhoon
5-9	Reserved
10	Dust/sandstorm
11-62	Reserved
63	Missing value

Note: New local names for storm of various strengths shall be added as necessary.

0 19 008

Vertical extent of circulation

Code figure	
0	Reserved
1	Shallow (top of circulation below 700 hPa level)
2	Medium (top between 700 hPa and 400 hPa level)
3	Deep (top above 400 hPa level)
4-6	Reserved
7	Missing value

0 19 010

Method for tracking the centre of synoptic feature code figure

Code figure	
1	Minimum value of sea level pressure
2	Maximum value of 850 hPa relative vorticity
3-14	Reserved
15	Missing value

0 20 003

Present weather

- 00-49 No precipitation at the station at the time of observation
- 00-19 No precipitation, fog, ice fog (except for 11 and 12), duststorm, sandstorm, drifting or blowing snow at the station at the time of observation or, except for 09 and 17, during the preceding hour

		Code figure			
No Meteors except photometeors	{	00	Cloud development not observed or not observable	}	
		01	Clouds generally dissolving or becoming less developed.		
		02	State of sky on the whole unchanged.		
Haze, dust, sand or smoke	{	03	Clouds generally forming or developing	}	
		04	Visibility reduced by smoke, e.g. veldt or forest fires, Industrial smoke or volcanic ashes		
		05	Haze		
		06	Widespread dust in suspension in the air, not raised by wind at or near the station at the time of observation		
		07	Dust or sand raised by wind at or near the station at the time of observation, but no well-developed dust whirl(s) or sand whirl(s), and no duststorm or sandstorm seen; or, In the case of sea stations and coastal stations, blowing spray at the station		
		08	Well-developed dust whirl(s) or sand whirl(s) seen at or near the station during the preceding hour or at the same time of observation, but no duststorm or sandstorm		
		09	Duststorm or sandstorm within sight at the time of observation, or at the station during the preceding hour		
		10	Mist		
		11	Patches		}
		12	More or less continuous		
		13	Lightning visible, no thunder heard		
		14	Precipitation within sight, not reaching the ground or the surface of the sea		
		15	Precipitation within sight, reaching the ground or the surface of the sea, but distant, i.e. estimated to be more than 5 km from the station		
		16	Precipitation within sight, reaching the ground or the surface of the sea, near to, but not at the station		
		17	Thunderstorm, but no precipitation at the time of observation		
		18	Squalls	}	
		19	Funnel cloud(s)**		At or within sight of the station during the preceding hour or at the time of observation
		20-29	Precipitation, fog, Ice fog or thunderstorm at the station during the preceding hour but not at the time of observation		

* The expression "at the station" refers to a land station or a ship.

** Tornado cloud or waterspout.

Code figure			
20	Drizzle (not freezing) or snow grains	}	not falling as shower(s)
21	Rain (not freezing)		
22	Snow		
23	Rain and snow or ice pellets		
24	Freezing drizzle or freezing rain		
25	Shower(s) of rain		
26	Shower(s) of snow, or of rain and snow		
27	Shower(s) of hail*, or of rain and hail*		
28	Fog or Ice fog		
29	Thunderstorm (with or without precipitation)		
30-39	Duststorm, sandstorm, drifting or blowing snow		
30	} Slight or moderate duststorm or sandstorm	-	has decreased during the preceding hour
31		-	no appreciable change during the preceding hour
32		-	has begun or has increased during the preceding hour
33	} Severe duststorm or sandstorm	-	has decreased during the preceding hour
34		-	no appreciable change during the preceding hour
35		-	has begun or has increased during the preceding hour
36	Slight or moderate drifting snow	}	generally low (below eye level)
37	Heavy drifting snow		
38	Slight or moderate blowing snow	}	generally high(above eye level)
39	Heavy blowing snow		
40-49	Fog or ice fog at the time of observation		
40	Fog or ice fog at a distance at the time of observation, but not at the station during the preceding hour, the fog or ice fog extending to a level above that of the observer		
41	Fog or ice fog in patches		
42	Fog or ice fog, sky visible	}	has become thinner during the preceding hour
43	Fog or ice fog, sky invisible		
44	Fog or ice fog, sky visible	}	no appreciable change during the preceding hour
45	Fog or ice fog, sky invisible		
46	Fog or ice fog, sky visible	}	has begun or has become thicker during the preceding hour
47	Fog or ice fog, sky invisible		
48	Fog, depositing rime, sky visible		
49	Fog, depositing rime, sky invisible		
50-99	Precipitation at the station at the time of observation		
50-59	Drizzle		
50	Drizzle, not freezing, intermittent	}	slight at time of observation
51	Drizzle, not freezing, continuous		
52	Drizzle, not freezing, intermittent	}	moderate at time of observation
53	Drizzle, not freezing, continuous		
54	Drizzle, not freezing, intermittent	}	heavy (dense) at time of observation
55	Drizzle, not freezing, continuous		
56	Drizzle, freezing, slight		
57	Drizzle, freezing, moderate or heavy (dense)		
58	Drizzle and rain, slight		
59	Drizzle and rain, moderate or heavy		

* Hail, small hail, snow pellets

Code figure			
60-69	Rain		
60	Rain, not freezing, intermittent	}	slight at time of observation
61	Rain, not freezing, continuous		
62	Rain, not freezing, intermittent	}	moderate at time observation
63	Rain, not freezing, continuous		
64	Rain, not freezing, intermittent	}	heavy at time of observation
65	Rain, not freezing, continuous		
66	Rain, freezing, slight		
67	Rain, freezing, moderate or heavy		
68	Rain or drizzle and snow, light		
69	Rain or drizzle and snow, moderate or heavy		
70-79	Solid precipitation not in showers		
70	Intermittent fall of snowflakes	}	slight at time of observation
71	Continuous fall of snowflakes		
72	Intermittent fall of snowflakes	}	moderate at time of observation
73	Continuous fall of snowflakes		
74	Intermittent fall of snowflakes	}	heavy at time of observation
75	Continuous fall of snowflakes		
76	Diamond dust (with or without fog)		
77	Snow grains (with or without fog)		
78	Isolated star-like snow crystals (with or without fog)		
79	Ice pellets		
80-99	Showery precipitation, or precipitation with current or recent thunderstorm		
80	Rain shower(s), slight		
81	Rain shower(s), moderate or heavy		
82	Rain shower(s), violent		
83	Shower(s) of rain and snow mixed, slight		
84	Shower(s) of rain and snow mixed, moderate or heavy		
85	Snow shower(s), slight		
86	Snow shower(s), moderate or heavy		
87	Shower(s) of snow pellets or small hail, with or without	}	- slight
88	rain or rain and snow mixed		- moderate or heavy
89	Shower(s) of hail, with or without rain or rain and snow	}	- slight
90	mixed, not associated with thunder		- moderate or heavy
91	Slight rain at time of observation	}	Thunderstorm during the preceding hour but not at time of observation
92	Moderate or heavy rain at time of observation.		
93	Slight snow, or rain and snow mixed or hail* at time of observation.		
94	Moderate or heavy snow, or rain and snow mixed or hail* at time of observation.	}	Thunderstorm at time of observation.
95	Thunderstorm, slight or moderate, without hail*, but with rain and/or snow at time of observation		
96	Thunderstorm, slight or moderate, with hail* at time of observation.		
97	Thunderstorm, heavy, without hail*, but with rain and/or snow at time of observation.		
98	Thunderstorm combined with duststorm or sandstorm at time of observation.		
99	Thunderstorm, heavy, with hail* at time of observation.		

* Hail, small hail, snow pellets.

Present weather reported from an automatic weather station

Code figure	
100	No significant weather observed
101	Clouds generally dissolving or becoming less developed during the past hour
102	State of sky on the whole unchanged during the past hour
103	Clouds generally forming or developing during the past hour
104	Haze or smoke, or dust in suspension in the air, visibility equal to, or greater than, 1km
105	Haze or smoke, or dust in suspension in the air, visibility less than 1 km
106-109	Reserved
110	Mist
111	Diamond dust
112	Distant lightning
113-117	Reserved
118	Squalls
119	Reserved
	Code figures 120-126 are used to report precipitation, fog (or ice fog) or thunderstorm at the station during the preceding hour but not at the time of observation
120	Fog
121	PRECIPITATION
122	Drizzle (not freezing) or snow grains
123	Rain (not freezing)
124	Snow
125	Freezing drizzle or freezing rain
126	Thunderstorm (with or without precipitation)
127	Blowing OR DRIFTING SNOW OR SAND
128	Blowing or drifting snow or sand, visibility equal to, or greater than, 1 km
129	Blowing or drifting snow or sand, visibility less than 1 km
130	FOG
131	Fog or ice fog in patches
132	Fog or ice fog, has become thinner during the past hour
133	Fog or ice fog, no appreciable change during the past hour
134	Fog or ice fog, has begun or become thicker during the past hour
135	Fog, depositing rime
136-139	Reserved
140	PRECIPITATION
141	Precipitation, slight or moderate
142	Precipitation, heavy
143	Liquid precipitation, slight or moderate
144	Liquid precipitation, heavy
145	Solid precipitation, slight or moderate
146	Solid precipitation, heavy
147	Freezing precipitation, slight or moderate
148	Freezing precipitation, heavy
149	Reserved
150	DRIZZLE
151	Drizzle, not freezing, slight
152	Drizzle, not freezing, moderate
153	Drizzle, not freezing, heavy
154	Drizzle, freezing, slight
155	Drizzle, freezing, moderate
156	Drizzle, freezing, heavy
157	Drizzle and rain, slight
158	Drizzle and rain, moderate or heavy

Code figure	
159	Reserved
160	RAIN
161	Rain, not freezing, slight
162	Rain, not freezing, moderate
163	Rain, not freezing, heavy
164	Rain, freezing, slight
165	Rain, freezing, moderate
166	Rain, freezing, heavy
167	Rain (or drizzle) and snow, slight
168	Rain (or drizzle) and snow, moderate or heavy
169	Reserved
170	SNOW
171	Snow, slight
172	Snow, moderate
173	Snow, heavy
174	Ice pellets, slight
175	Ice pellets, moderate
176	Ice pellets, heavy
177-179	Reserved
180	SHOWER(S) or intermittent PRECIPITATION
181	Rain shower(s) or intermittent rain, slight
182	Rain shower(s) or intermittent rain, moderate
183	Rain shower(s) or intermittent rain, heavy
184	Rain shower(s) or intermittent rain, violent
185	Snow shower(s) or intermittent snow, slight
186	Snow shower(s) or intermittent snow, moderate
187	Snow shower(s) or intermittent snow, heavy
188-189	Reserved
190	THUNDERSTORM
191	Thunderstorm, slight or moderate, with no precipitation
192	Thunderstorm, slight or moderate, with rain showers and/or snow showers
193	Thunderstorm, slight or moderate, with hail
194	Thunderstorm, heavy, with no precipitation
195	Thunderstorm, heavy, With rain showers and/or snow showers
196	Thunderstorm, heavy, with hail
197-198	Reserved
199	Tornado
	Present weather (In addition to present weather report from either a manned or an automatic station)

Decile 200-209

200	Not used
201	Not used
202	Not used
203	Not used
204	Volcanic ash suspended In the air aloft
205	Not used
206	Thick dust haze, visibility less than 1 km
207	Blowing spray at the station
208	Drifting dust (sand)
209	Wall of dust or sand in distance (like haboob)

Code
figure

Decile 210-219

210	Snow haze
211	Whiteout
212	Not used
213	Lightning, cloud to surface
214-216	Not used
217	Dry thunderstorm
218	Not used
219	Tornado cloud (destructive) at or within sight of the station during preceding hour or at the time of observation

Decile 220-229

220	Deposition of volcanic ash
221	Deposition of dust or sand
222	Deposition of dew
223	Deposition of wet snow
224	Deposition of soft rime
225	Deposition of hard rime
226	Deposition of hoarfrost
227	Deposition of glaze
228	Deposition of ice crust (ice slick)
229	Not used

Decile 230-239

230	Duststorm or sandstorm with temperature below 0°C
231-238	Not used
239	Blowing snow, impossible to determine whether snow is falling or not

Decile 240-249

240	Not used
241	Fog on sea
242	Fog in valleys
243	Arctic or Antarctic sea smoke
244	Steam fog (sea, lake or river)
245	Steam log (land)
246	Fog over ice or snow cover
247	Dense fog, visibility 60-90 m
248	Dense fog, visibility 30-60 m
249	Dense fog, visibility less than 30 m

Decile 250-259

250	Drizzle, rate of fall	{	less than 0.10 mm h ⁻¹
251			0.10-0.19 mm h ⁻¹
252			0.20-0.39 mm h ⁻¹
253			0.40-0.79 mm h ⁻¹
254			0.80-1.59 mm h ⁻¹
255			1.60-3.19 mm h ⁻¹
256			3.20-6.39 mm h ⁻¹
257			6.4 mm h ⁻¹ or more
258	Not used		
259	Drizzle and snow		

Code figure		
Decile 260-269		
260	} Rain, rate of fall	} less than 1.0 mm h ⁻¹ 1.- 1.9 mm h ⁻¹ 2.- 3.9 mm h ⁻¹ 4.- 7.9 mm h ⁻¹ 8.-15.9 mm h ⁻¹ 16.0-31.9 mm h ⁻¹ 32.0-63.9 mm h ⁻¹ 64.0 mm h ⁻¹ or more
261		
262		
263		
264		
265		
266		
267		
268-269	Not used	
Decile 270-279		
270	} Snow, rate of fall	} less than 1.0 cm h ⁻¹ 1.0-1.9 cm h ⁻¹ 2.0-3.9 cm h ⁻¹ 4.0-7.9 cm h ⁻¹ 8.0-15.9 cm h ⁻¹ 16.0-31.9 cm h ⁻¹ 32.0-63.9 cm h ⁻¹ 64.0 cm h ⁻¹ or more
271		
272		
273		
274		
275		
276		
277		
278	Snow or Ice crystal precipitation from a clear sky	
279	Wet snow, freezing on contact	
Decile 280-299		
280	Precipitation of rain	
281	Precipitation of rain, freezing	
282	Precipitation of rain and snow mixed.	
283	Precipitation of snow	
284	Precipitation of snow pellets or small hail	
285	Precipitation of snow pellets or small hail, with rain	
286	Precipitation of snow pellets or small hail, with rain and snow mixed	
287	Precipitation of snow pellets or small hail, with snow	
288	Precipitation of hail	
289	Precipitation of hail, with rain	
290	Precipitation of hail, with rain and snow mixed	
291	Precipitation of hail, with snow	
292	Shower(s) or thunderstorm over sea	
293	Shower(s) or thunderstorm over mountains	
294-299	Not used	
300-507	Reserved	
508	No significant phenomenon to report, present and past weather omitted	
509	No observation, data not available, present and past weather omitted	
510	Present and past weather missing, but expected	
511	Missing value	

Notes:

- (1) The middle portion of this code table (code figures 100-199) includes terms on several levels to cover simple and increasingly complex automatic stations.
- (2) Generic terms for weather (e.g. fog, drizzle) are intended for use at automatic stations capable of determining types of weather but no other information. Generic terms are included in the code table using all capital letters.
- (3) Code figures for generic precipitation (code figures 140-148) are arranged in order of increasing complexity. For example, a very simple station that can sense only the presence or absence of precipitation would use code figure 140 (precipitation). At the next level, an automatic station capable of sensing amount but not type would use code figure 141 or 142. An automatic station capable of sensing gross type (liquid, solid, freezing) and amount would use code figures 143-148. An automatic station capable of reporting actual types of

precipitation (e.g. drizzle rain), but not the amount, would use the appropriate whole decile number (e.g. 150 for generic drizzle, 160 for generic rain).

0 20 004/0 20 005

Past weather (1) and (2)

Code
figure

0	Cloud covering 1/2 or less of the sky throughout the appropriate period
1	Cloud covering more than 1/2 of the sky during part of the appropriate period and covering 1/2 or less during part of the period
2	Cloud covering more than 1/2 of the sky throughout the appropriate period
3	Sandstorm, duststorm or blowing snow
4	Fog or ice fog or thick haze
5	Drizzle
6	Rain
7	Snow, or rain and snow mixed
8	Shower(s)
9	Thunderstorm(s) with or without precipitation
10	No significant weather observed
11	Visibility REDUCED
12	Blowing phenomena, visibility reduced
13	FOG
14	PRECIPITATION
15	Drizzle
16	Rain
17	Snow or ice pellets
18	Showers or intermittent precipitation
19	Thunderstorm
20-30	Reserved
31	Missing value

Note: The weather descriptions in code figures 10 to 19 are progressively complex, to accommodate the different levels of weather discrimination capability of various automatic stations. Stations having only basic sensing capability may use the lower code figures and basic generic descriptions (shown in capital letters). Stations with progressively higher discrimination capability shall use the more detailed descriptions (higher codes).

0 20 008

Cloud Distribution for Aviation

code figure		
0	Sky Clear	
1	Few	
2	Scattered	
3	Broken	
4	Overcast	
5	Reserved	
6	Scattered/Broken	(Many forecasts use Scattered/Broken or
7	Broken/Overcast	(Broken/Overcast followed by cloud type(s))
8	Isolated	(Used on aviation charts to describe the cloud type Cb)
9	Isolated embedded	(Used on aviation charts to describe the cloud type Cb)
10	Occasional	(Used on aviation charts to describe the cloud type Cb)
11	Occasional embedded	(Used on aviation charts to describe the cloud type Cb)
12	Frequent	(Used on aviation charts to describe the cloud type Cb)
13	Dense	(Used on aviation charts to describe cloud that would cause sudden changes in visibility (less than 1000m))
14	Layers	
15-30	Reserved	
31	Missing value	

0 20 009

General Weather Indicator (TAF/METAR)

Code figure	
0	Reserved
1	NSC Nil Significant Cloud
2	CAVOK
3	SKC Sky Clear
4	NSW Nil Significant Weather
5-14	Reserved
15	Missing value

0 20 011

Cloud amount

Code
figure

0	0	0
1	1 okta or less, but not zero	1/10 or less, but not zero
2	2 oktas	2/10 - 3/10
3	3 oktas	4/10
4	4 oktas	5/10
5	5 oktas	6/10
6	6 oktas	7/10 - 8/10
7	7 oktas or more, but not 8 oktas	9/10 or more, but not 10/10
8	8 oktas	10/10
9	Sky obscured by fog and/or other meteorological phenomena	
10	Sky partially obscured by fog and/or other meteorological phenomena	
11	Scattered	
12	Broken	
13	Few	
14	Reserved	
15	Cloud cover is Indiscernible for reasons other than fog or other meteorological phenomena, or observation is not made	

Notes:

- (1) For use of code figure 15, see Regulation 12.1.4.
- (2) 'Clear' and 'overcast' are coded by 0 and 8 respectively.

0 20 012

Cloud type

Code figure	
0	Cirrus (Ci)
1	Cirrocumulus (Cc)
2	Cirrostratus (Cs)
3	Alto cumulus (Ac)
4	Altostratus (As)
5	Nimbostratus (Ns)
6	Stratocumulus (Sc)
7	Stratus (St)
8	Cumulus (Cu)
9	Cumulonimbus (Cb)
10	No C _H clouds
11	Cirrus fibratus, sometimes uncinus, not progressively invading the sky
12	Cirrus spissatus, in patches or entangled sheaves, which usually do not increase and sometimes seem to be the remains of the upper part of a Cumulonimbus; or Cirrus castellanus or floccus
13	Cirrus spissatus cumulonimbogenitus
14	Cirrus uncinus or fibratus, or both, progressively invading the sky; they generally thicken as a whole
15	Cirrus (often in bands) and Cirrostratus, or Cirrostratus alone, progressively invading the sky; they generally thicken as a whole, but the continuous veil does not reach 45 degrees above the horizon
16	Cirrus (often in bands) and Cirrostratus, or Cirrostratus alone, progressively Invading the sky; they generally thicken as a whole; the continuous veil extends more than 45 degrees above the horizon, without the sky being totally covered
17	Cirrostratus covering the whole sky
18	Cirrostratus not progressively invading the sky and not entirely covering It
19	Cirrocumulus alone, or Cirrocumulus predominant among the C _H clouds
20	No C _M clouds
21	Altostratus translucidus
22	Altostratus opacus or Nimbostratus
23	Alto cumulus translucidus at a single level
24	Patches (often Lenticular) of Alto cumulus translucidus, continually changing and occurring at one or more levels
25	Alto cumulus translucidus in bands, or one or more layers of Alto cumulus translucidus or opacus, progressively Invading the sky; these Alto cumulus clouds generally thicken as a whole
26	Alto cumulus cumulogenitus (or cumulonimbogenitus)
27	Alto cumulus translucidus or opacus In two or more layers, or Alto cumulus opacus In a single layer, not progressively Invading the sky, or Alto cumulus with Altostratus or Nimbostratus
28	Alto cumulus castellanus or floccus
29	Alto cumulus of a chaotic sky, generally at several levels
30	No C _L clouds
31	Cumulus humilis or Cumulus fractus other than of bad weather,* or both
32	Cumulus mediocris or congestus, Towering cumulus (TCU), with or without Cumulus of species fractus or humilis or Stratocumulus, all having their bases at the same level
33	Cumulonimbus calvus, with or without Cumulus, Stratocumulus or Stratus
34	Stratocumulus cumulogenitus
35	Stratocumulus other than Stratocumulus cumulogenitus
36	Stratus nebulosus or Stratus fractus other than of bad weather*, or both
37	Stratus fractus or Cumulus fractus of bad weather*, or both (pannus), usually below Altostratus or Nimbostratus
38	Cumulus and Stratocumulus other than Stratocumulus cumulogenitus, with bases at different levels
39	Cumulonimbus capillatus (often with an anvil), with or without Cumulonimbus calvus, Cumulus, Stratocumulus, Stratus or pannus
40	CH

Code figure	
41	CM
42	CL
43-58	Reserved
59	Cloud not visible owing to darkness, fog, duststorm, sandstorm, or other analogous phenomena
60	C _H clouds Invisible owing to darkness, fog, blowing dust or sand, or other similar phenomena, or because of a continuous layer of lower clouds
61	C _M clouds Invisible owing to darkness, fog, blowing dust or sand, or other similar phenomena, or because of continuous layer of lower clouds
62	C _L clouds invisible owing to darkness, fog, blowing dust or sand, or other similar phenomena
63	Missing value

* "Bad weather" denotes the conditions which generally exist during precipitation and a short time before and after.

0 20 017

Cloud top description

Code figure		
0	Isolated cloud fragments of clouds	
1	Continuous cloud	} flat tops
2	Broken cloud - small breaks	
3	Broken cloud - large breaks	} undulating tops
4	Continuous cloud	
5	Broken cloud - small breaks	
6	Broken cloud - large breaks	
7	Continuous or almost continuous waves with towering clouds above the top of the layer	
8	Groups of waves with towering clouds above the top of the layer	
9	Two or more layers at different levels	
10-14	reserved	
15	Missing value	

0 20 018

Tendency of runway visual range

Code figure	
0	Increasing (U)
1	Decreasing (D)
2	No distinct change (N)
3	Missing value

0 20 021***Type of precipitation***

Bit No.	
1	Precipitation-unknown type
2	Liquid precipitation not freezing
3	Liquid freezing precipitation
4	Drizzle
5	Rain
6	Solid precipitation
7	Snow
8	Snow grains
9	Snow pellets
10	Ice pellets
11	Ice crystals
12	Diamond dust
13	Small hail
14	Hail
15	Glaze
16	Rime
17	Soft rime
18	Hard rime
19	Clear ice
20	Wet snow
21	Hoar frost
22	Dew
23-29	Reserved
All 30	Missing value

Note: Mixed precipitation is indicated by setting to one the bits of all the observed single types of precipitation

0 20 022***Character of precipitation***

Code figure	
0	No precipitation
1	Continuous
2	Intermittent
3	Shower
4	Not reaching ground
5	Deposition
6-14	Reserved
15	Missing value

0 20 023

Other weather phenomena

Bit No.	
1	Dust/sand whirl
2	Squalls
3	Sand storm
4	Dust storm
5	Lightning - cloud to surface
6	Lightning - cloud to cloud
7	Lightning - distant
8	Thunderstorm
9	Funnel Cloud not touching surface
10	Funnel cloud touching surface
11	Spray
12-17	Reserved
All 18	Missing value

0 20 024

Intensity of phenomena

Code figure	
0	No phenomena
1	Light
2	Moderate
3	Heavy
4	Violent
5-6	Reserved
7	Missing value

0 20 025

Obscuration

Bit No.	
1	Fog
2	Ice fog
3	Steam fog
4-6	Reserved
7	Mist
8	Haze
9	Smoke
10	Volcanic ash
11	Dust
12	Sand
13	Snow
14-20	Reserved
All 21	Missing value

0 20 026

Character of obscuration

Code figure	
0	No change
1	Shallow
2	Patches
3	Partial
4	Freezing
5	Low drifting
6	Blowing
7	Increasing
8	Decreasing
9	In suspension in the air
10	Wall
11	Dense
12	Whiteout
13-14	Reserved
15	Missing value

0 20 027

Phenomena occurrence

Bit No.	
1	At time of observation
2	In past hour
3	In time period for past weather W_1W_2
4	In time period specified
5-6	Reserved
7	At the station
8	In the vicinity
All 9	Missing value

Note : Phenomenon in 0 20 027 means any phenomenon, including precipitation and obscuration.

0 20 032

Rate of ice accretion

Code figure	
0	Ice not building up
1	Ice building up slowly
2	Ice building up rapidly
3	Ice melting or breaking up slowly
4	Ice melting or breaking up rapidly
5-6	Reserved
7	Missing value

0 20 033

Cause of ice accretion

Bit No.	
1	Icing from ocean spray
2	Icing from fog
3	Icing from rain
All 4	Missing value

0 20 034

Sea Ice concentration

Code figure			
0	No sea ice in sight		
1	Ship in open lead more than 1.0 nautical mile wide, or ship in fast ice with boundary beyond limit of visibility		
2	Sea ice present in concentrations less than 3/10 (3/8) open water or very open pack ice	Sea ice concentration is uniform in the observation area	Ship in ice or within 0.5 nautical mile of ice edge
3	4/10 to 6/10 (3/8 to less than 6/8), open pack ice		
4	7/10 to 8/10 (6/8 to less 7/8), close pack ice		
5	9/10 or more, but not 10/10 (7/8 to less than 8/8), very close pack ice		
6	Strips and patches of pack ice with open water between	Sea ice concentration is not uniform in the observation area	
7	Strips and patches of close or very close pack ice with areas of lesser concentration between		
8	Fast ice with open water, very open or open pack ice to seaward of the ice boundary		
9	Fast ice with close or very close pack ice to seaward of the boundary		
10-13	Reserved		
14	Unable to report, because of darkness, lack of visibility, or because ship is more than 0.5 nautical mile away from ice edge		
15-30	Reserved		
31	Missing value		

0 20 035

Amount and type of Ice

Code
figure

0	No ice of land origin
1	1-5 icebergs, no growlers or bergy bits
2	6-10 icebergs, no growlers or bergy bits
3	11-20 Icebergs, no growlers or bergy bits
4	Up to and Including 10 growlers and bergy bits - no icebergs
5	More than 10 growlers and bergy bits - no Icebergs
6	1-5 icebergs, with growlers and bergy bits
7	6-10 icebergs, with growlers and bergy bits
8	11-20 icebergs, with growlers and bergy bits
9	More than 20 Icebergs, with growlers and bergy bits - a major hazard to navigation
10-13	Reserved
14	Unable to report, because of darkness, lack of visibility or because only sea ice is visible
15	Missing value

0 20 036

Ice situation

Code
figure

0	Ship in open water with floating ice in sight
1	Ship In easily penetrable ice; conditions improving
2	Ship In easily penetrable ice; conditions not changing
3	Ship in easily penetrable ice; conditions worsening
4	Ship in ice difficult to penetrate; conditions improving
5	Ship in ice difficult to penetrate; conditions not changing
6	Ship in ice difficult to penetrate and conditions worsening. Ice forming and floe freezing together
7	Ship in ice difficult to penetrate and conditions worsening. Ice under slight pressure
8	Ship in ice difficult to penetrate and conditions worsening. Ice under moderate or severe pressure
9	Ship in ice difficult to penetrate and conditions worsening. Ship beset
10-29	Reserved
30	Unable to report, because of darkness or lack of visibility
31	Missing value

0 20 037

Ice development

Code
figure

0	New ice only (frazil ice, grease ice, slush, shuga)
1	Nilas or ice rind, less than 10 cm thick
2	Young ice (grey ice, grey-white ice), 10-30 cm thick
3	Predominantly new and/or young ice with some first-year ice
4	Predominantly thin first-year ice with some new and/or young ice
5	All thin first-year ice (30-70 cm thick)
6	Predominantly medium first-year ice (70-120 cm thick) and thick first-year ice (>120 cm thick) with some thinner (younger) first-year ice
7	All medium and thick first-year ice
8	Predominantly medium and thick first-year ice with some old ice (usually more than 2 metres thick)
9	Predominantly old ice
11-29	Reserved
30	Unable to report, because of darkness, lack of visibility or because only ice of land origin is visible or because ship is more than 0.5 nautical mile away from ice edge
31	Missing value

0 20 041

Airframe Icing

Code
figure

0	No icing
1	Light icing
2	Light icing In cloud
3	Light icing In precipitation
4	Moderate icing
5	Moderate icing in cloud
6	Moderate icing in precipitation
7	Severe icing
8	Severe icing in cloud
9	Severe icing in precipitation
10	Trace of icing
11	Trace of icing in cloud
12	Trace of icing in precipitation
13-14	Reserved
15	Missing value

0 20 062

State of the ground

Code figure		
0	Surface of ground dry (without cracks and no appreciable amount of dust or loose sand)	}
1	Surface of ground moist	
2	Surface of ground wet (standing water in small or large pools on surface)	
3	Flooded	
4	Surface of ground frozen	
5	Glaze on ground	
6	Loose dry dust or sand not covering ground completely	
7	Thin cover of loose dry dust or sand covering ground completely	
8	Moderate or thick cover of loose dry dust or sand covering ground completely	
9	Extremely dry with cracks	
10	Ground predominantly covered by ice	}
11	Compact or wet snow (with or without ice) covering less than one-half of the ground	
12	Compact or wet snow (with or without ice) covering at least one-half of the ground but ground not completely covered	
13	Even layer of compact or wet snow covering ground completely	
14	Uneven layer of compact or wet snow covering ground completely	
15	Loose dry snow covering less than one-half of the ground	
16	Loose dry snow covering at least one-half of the ground (but not completely)	
17	Even layer of loose dry snow covering ground completely	
18	Uneven layer of loose dry snow covering ground completely	
19	Snow covering ground completely; deep drifts	
20-30	Reserved	}
31	Missing value	

Notes:

- (1) The definitions in code numbers 0 to 2 and 4 apply to representative bare ground and numbers 3, 5 to 9 and 10 to 19 to an open representative area.
- (2) In all instances the highest code figures applicable are to be reported.
- (3) In the above code table, whenever reference is made to ice, it also includes solid precipitation other than snow.

0 20 063

Special phenomena

(To be developed)

0 20 071***Accuracy of fix and rate of atmospheric***

Code figure	Accuracy of fix (estimated error)	Repetition rate
0	No assessment	No assessment
1	Less than 50 km	Less than 1 per second
2	Between 50 and 200 km	Less than 1 per second
3	More than 200 km	Less than 1 per second
4	Less than 50 km	1 or more per second
5	Between 50 and 200 km	1 or more per second
6	More than 200 km	1 or more per second
7	Less than 50 km	Rate so rapid number cannot be counted
8	Between 50 and 200 km	Rate so rapid number cannot be counted
9	More than 200 km	Rate so rapid number cannot be counted
10-14	Reserved	
15	Missing value	

0 20 090***Special clouds***

Code figure	
0	Reserved
1	Nacreous clouds
2	Noctilucent clouds
3	Clouds from waterfalls
4	Clouds from fires
5	Clouds from volcanic eruptions
6-14	Reserved
15	Missing value

0 21 066

Wave Scatterometer Product Confidence

Bit No.	
1	Process equipment not working
2	Equipment failed
3	PRF code changed during image generation
4	Sampling window changed during image generation
5	Gain changed during image generation
6	Chirp replica exceeds specified values
7	Input data mean & standard deviation of in-phase & quadrature out of range
8	Doppler centroid confidence > MMCC value
9	Doppler centroid absolute value > PRF/2
10	Doppler ambiguity confidence < MMCC value
11	Output data mean and standard deviation =< MMCC value
All 12	Missing value

Notes:

- (1) MMCC is Mission Management Control Centre
- (2) PRF is Pulse Repetition Frequency

0 21 067

Wind Scatterometer Product Confidence Data

Bit No.	
1	No forebeam calculation
2	No midbeam calculation
3	No aftbeam calculation
4	Forebeam arcing detected
5	Midbeam arcing detected
6	Aftbeam arcing detected
7	Any beam noise content above or equal to threshold
8	Land (any land in cell footprint)
9	Autonomous ambiguity removal not used
10	Meteorological background not used
11	Minimum residual exceeded threshold
12	Frame checksum error detected
All 13	Missing Value

0 21 068

Radar Altimeter Product Confidence Data

Bit No.	
1	Standard deviation wind speed outside MMCC limit
2	Standard deviation Significant wave height outside MMCC limit
3	Standard deviation altitude outside MMCC limit
4	Mean peakiness outside MMCC limit
5	Frame checksum error detected
6	Height-time loop time constant correction not performed
7	Not enough measurements (N<10)
All 8	Missing Value

Note: MMCC is Mission Management Control Centre.

0 21 069

SST product confidence data

Bit No.	
1	12.0 :m channel present in source data
2	11.0 :m channel present in source data
3	3.7 :m channel present in source data
4	1.6 :m channel present in source data
5	Cloud-identification used 1.6 um histogram reflectance cloud test
6	1.6 :m histogram reflectance cloud test used dynamic threshold
7	Sun glint detected by 1.6 um reflectance cloud test
8	3.7 :m channel used in sea-surface temperature retrieval
9	Sea-surface temperature derivation used day-time data (night-time if zero)
All 10	Missing value


0 21 070

SST product confidence data (SADIST-2)

Bit Meaning when set


1-9 *Nadir-only view SST retrieval used 3.7 micron channel (one bit per 10-arcmin cell)*

- 1 Cell 1:nadir-only view SST used 3.7 micron channel
- 2 Cell 2:nadir-only view SST used 3.7 micron channel
- 3 Cell 3:nadir-only view SST used 3.7 micron channel
- 4 Cell 4:nadir-only view SST used 3.7 micron channel
- 5 Cell 5:nadir-only view SST used 3.7 micron channel
- 6 Cell 6:nadir-only view SST used 3.7 micron channel
- 7 Cell 7:nadir-only view SST used 3.7 micron channel
- 8 Cell 8:nadir-only view SST used 3.7 micron channel
- 9 Cell 9:nadir-only view SST used 3.7 micron channel



10-18 *Dual view SST retrieval used 3.7 micron channel (one bit per 10-arcmin cell)*

- 10 Cell 1:nadir-only view SST used 3.7 micron channel
- 11 Cell 2:nadir-only view SST used 3.7 micron channel
- 12 Cell 3:nadir-only view SST used 3.7 micron channel
- 13 Cell 4:nadir-only view SST used 3.7 micron channel
- 14 Cell 5:nadir-only view SST used 3.7 micron channel
- 15 Cell 6:nadir-only view SST used 3.7 micron channel
- 16 Cell 7:nadir-only view SST used 3.7 micron channel
- 17 Cell 8:nadir-only view SST used 3.7 micron channel
- 18 Cell 9:nadir-only view SST used 3.7 micron channel



- 19 Nadir view contains day-time data (night if zero)
- 20 Forward view contains day-time data (night if zero)
- 21 Record contains contributions from instrument scans acquired when ERS platform not in yaw-steering mode
- 22 Record contains contributions from instrument scans for which Product Confidence Data show quality is poor or unknown
- All 23 Missing value

0 21 072

Altimeter Calibration Status

Bit No.	
1	Height error correction applied instead of open loop calibration
2	Microwave sounder used for troposphere correction
3	AGC output correction applied instead of open loop calibration
All 4	Missing value

0 21 073

Altimeter Instrument Mode

Bit No.	
1	Blank data record
2	Test
3	Calibration (closed loop)
4	BITE
5	Acquisition on ice
6	Acquisition on ocean
7	Tracking on ice
8	Tracking on ocean
All 9	Missing value

0 21 076

Representation of intensities

Code figure	
1	Linear
2	Logarithmic (base e)
3	Logarithmic (base 10)
3-6	Reserved
7	Missing value

0 21 109

SEAWINDS wind vector call quality

Bit No.	
1	Not enough good sigma-0 available for wind retrieval
2	Poor azimuth diversity among sigma-0 for wind retrieval
3-7	Reserved
8	Some portion of wind vector cell is over land
9	Some portion of wind vector cell is over ice
10	Wind retrieval not performed for wind vector cell
11	Reported wind speed is greater than 30 m s ⁻¹
12	Reported wind speed is less than or equal to 3 m s ⁻¹
13-16	Reserved
All 17	Missing value

0 21 115

SEAWINDS sigma-0 quality

Bit No.	
1	Sigma-0 measurement is not usable
2	Signal to noise ratio is low
3	Sigma-0 is negative
4	Sigma-0 is outside of acceptable range
5	Scattermeter pulse quality is not acceptable
6	Sigma-0 cell location algorithm does not converge
7	Frequency shift lies beyond the range of the x factor table
8	Spacecraft temperature is beyond calibration coefficient range
9	No applicable altitude records were found for this sigma-0
10	Interpolated ephemeris data are not acceptable for this sigma-0
11-16	Reserved
All 17	Missing value

0 21 116

SEAWINDS sigma-0 mode

Bit No.	
1	Calibration/measurement pulse flag (1)
2	Calibration/measurement pulse flag (2)
3	Outer antenna beam
4	Sigma-0 cell is aft of spacecraft
5	Current mode (1)
6	Current mode (2)
7	Effective gate width - slice resolution (1)
8	Effective gate width - slice resolution (2)
9	Effective gate width - slice resolution (3)
10	Low resolution mode - whole pulse data
11	Scatterometer electronic subsystem B
12	Alternate spin rate - 19.8 rpm
13	Receiver protection on
14	Slices per composite flag (1)
15	Slices per composite flag (2)
16	Slices per composite flag (3)
All 17	Missing value

Wind scatterometer geophysical model function

Code figure	
0	Reserved
1	SASS
2	SASS2
3	NSCAT0
4	NSCAT1
5	NSCAT2
6	QSCAT0
7	QSCAT1
8-30	Reserved
31	CMOD1
32	CMOD2
33	CMOD3
34	CMOD4
35	CMOD5
36-62	Reserved
63	Missing value

0 22 056

Direction of profile

Code figure	
0	Upwards profile
1	Downwards profile
2	Horizontal
3	Missing value

0 22 061

State of the sea

Code figure	Descriptive terms	Height in metres
0	Calm (glassy)	0
1	Calm (rippled)	0-0.1
2	Smooth (wavelets)	0.1-0.5
3	Slight	0.5-1.25
4	Moderate	1.25-2.5
5	Rough	2.5-4
6	Very rough	4-6
7	High	6-9
8	Very high	9-14
9	Phenomenal	Over 14
10-14	Reserved	
15	Missing value	

Notes:

- (1) These values refer to well-developed wind waves of the open sea. While priority shall be given to the descriptive terms, these height values may be used for guidance by the observer when reporting the total state of agitation of the sea resulting from various factors such as wind, swell, currents, angle between swell and wind, etc.
- (2) The exact bounding height shall be assigned for the lower code figure; e.g., a height of 4 m is coded as 5.

0 22 067

Instrument type for water temperature profile measurement

(See common Code Table C-3)

0 22 068

Water temperature profile recorder types

(See common Code Table C-4)

0 22 120

Tide station automated water level check

Code
figure

0	Good data
1	Maximum (high) water level limit exceeded
2	Minimum (low) water level limit exceeded
3	Rate of change limit for water level exceeded
4	Flat limit for water level exceeded
5	Observed minus predicted water level value limit exceeded
6	Observed value from primary water level sensor minus backup water level sensor
7	Value exceeded specified tolerance from expected value
8	Water level QA parameter (sigmas and/or outliers) limits exceeded
9	Sea temperature outside of expected range
10	Multiple QC checks (above) failed
11	No automated water level checks performed
12-30	Reserved
31	Missing value

0 22 121

Tide station manual water level check

Code
figure

0	Operational
1	Possible clogging problem or otherwise degraded water level data
2	Possible datum shift
3	Unknown status of water level sensor
4	Suspected or known sea temperature sensor problem
5	Multiple possible problems (above)
6	Bad data - DO NOT DISSEMINATE!
7	No manual water level checks performed
8-30	Reserved
31	Missing value

0 22 122

Tide station automated meteorological data check

Code
figure

0	Good data from all sensors
1	Wind direction outside of allowable range
2	Wind speed outside of expected range
3	Barometric pressure outside of expected range
4	Air temperature outside of expected range
5	Multiple sensors failed QC checks
6	No automated meteorological data checks performed
7-30	Reserved
31	Missing value

Tide station manual meteorological data check

Code
figure

0	Operational
1	Suspected or known problem with wind sensor
2	Suspected or known problem with barometric pressure sensor
3	Suspected or known problem with air temperature sensor
4	Unknown status of all sensors
5	Suspected or known problems with multiple sensors
6	Bad data - DO NOT DISSEMINATE!
7	No manual meteorological data checks performed
8-30	Reserved
31	Missing value

0 23 001

Accident early notification - article applicable

Code
figure

0	Reserved
1	Articles 1 and 2
2	Article 3
3	Article 5.2
4-6	Reserved
7	Missing value

0 23 002

Activity or facility involved In Incident

Code
figure

0	Reserved
1	Nuclear reactor on ground
2	Nuclear reactor at sea
3	Nuclear reactor In space
4	Nuclear fuel facility
5	Radioactive waste management facility
6	Transport of nuclear fuel or radioactive waste
7	Storage of nuclear fuel or radioactive waste
8	Manufacture of radio-isotopes
9	Use of radio-isotopes
10	Storage of radio-isotopes
11	Disposal of radio-isotopes
12	Transport of radio-isotopes
13	Use of radio-isotopes for power generation
14-29	Reserved
30	Other
31	Missing value

0 23 003

Type of release

Code
figure

0	No release
1	Release to atmosphere
2	Release to water
3	Release to both atmosphere and water
4	Expected release to atmosphere
5	Expected release to water
6	Expected release to both atmosphere and water
7	Missing value

0 23 004

Countermeasures taken near border

Code
figure

0	No countermeasures
1	Evacuation
2	Sheltering
3	Prophylaxis
4	Water
5-6	Reserved
7	Missing value

0 23 005

Cause of incident

Code
figure

0	Incident State does not understand what happened
1	Incident State knows the cause of the incident
2	Reserved
3	Missing value

0 23 006

Incident situation

Code
figure

0	No improvement
1	Unstable
2	No deterioration
3	Improving
4	Stable
5	Deteriorating
6	Reserved
7	Missing value

0 23 007

Characteristics of release

Code
figure

0	No release
1	Release has stopped
2	Release
3	Release is continuing
4-6	Reserved
7	Missing value

0 23 008 / 0 23 009

State of current or expected release

Code
figure

- 0 Gaseous
- 1 Particulate
- 2 Mixture of gaseous and particulate
- 3 Missing value

0 23 016

Possibility of significant chemical toxic health effect

Code
figure

- 0 No significant chemical toxic health effect
- 1 Significant chemical toxic health effect possible
- 2 Reserved
- 3 Missing value

0 23 018

Release behaviour over time

Code
figure

- 0 Release no longer occurring
- 1 Release still occurring
- 2 Release expected to increase in next 6 hours
- 3 Release expected to remain constant in next 6 hours
- 4 Release expected to decrease in next 6 hours
- 5-6 Reserved
- 7 Missing value

0 23 031

Possibility that plume will encounter precipitation in State in which incident occurred

Code
figure

- 0 Plume will not encounter rain in incident State
- 1 Plume will encounter rain in incident State
- 2 Reserved
- 3 Missing value

0 23 032

Plume will encounter change in wind direction and/or speed flag

Code
figure

- 0 No significant change expected within the next 6 hours
- 1 Anticipated significant change expected within the next 6 hours
- 2 Reserved
- 3 Missing value

0 24 003

Composition of release

Code
figure

0	Noble gases
1	Iodides
2	Caesiums
3	Transuranics
4-30	Reserved
31	Missing value

0 25 004

Echo processing

Code
figure

- 0 Incoherent
- 1 Coherent (Doppler)
- 2 Reserved
- 3 Missing value

0 25 005

Echo Integration

Code
figure

- 0 Logarithm - 2.5dB
- 1 Linear
- 2 Special
- 3 Missing value

0 25 006

Z to R conversion

Code
figure

- 0 ZH to R conversion
- 1 (ZH, ZDR) to (NO, DO) to R
- 2 (Z (F1), Z (F2)) to attenuation to R
- 3-5 Reserved
- 6 Other
- 7 Missing value

0 25 009

Calibration method

Bit No.

- 1 None
- 2 Calibration target or signal
- 3 Against rain gauges
- 4 Against other Instruments (distrometer - attenuation)
- All 4 Missing value

0 25 010

Clutter treatment

Code
figure

0	None
1	Map
2	Insertion of higher elevation data and map
3	Analysis of the fluctuating Logarithm signal (clutter detection)
4	Extraction of the fluctuating part of linear signal (clutter suppression)
5	Clutter suppression - Doppler
6	Multi-parameter analysis
7-14	Reserved
15	Missing value

0 25 011

Ground occultation correction (screening)

Code
figure

0	None
1	Map of correction factors
2	Interpolation (azimuth or elevation)
3	Missing value

0 25 012

Range Attenuation Correction

Code
figure

0	Hardware
1	Software
2	Hardware and software
3	Missing value

0 25 013

Bright-band correction

Bit No.

1	Brightband correction
all 2	Missing value

0 25 015

Radome Attenuation Correction

Bit No.

1	Radome Attenuation Correction
All 2	Missing value

0 25 017

Precipitation attenuation correction

Bit No.	
1	Precipitation attenuation correction
All 2	Missing value

0 25 020

Mean-speed estimation

Code figure	
0	FFT (fast Fourier transform)
1	PP (pulse-pair processing)
2	VPC (vector-phase change)
3	Missing value

0 25 021

Wind computation enhancement

Bit No.	
1	Simple average
2	Consensus average
3	Median check
4	Vertical consistency check
5	Other
6-7	Reserved
All 8	Missing value

0 25 030

Running mean sea-surface temperature usage

Code figure	
0	Running mean sea-surface temperature not used because usage criteria not met
1	Running mean sea-surface temperature not used because data not available
2	Running mean sea-surface temperature used as predictor
3	Missing value

0 25 032

NOAA wind profiler mode information

Code figure	
0	Reserved
1	Data from low mode
2	Data from high mode
3	Missing value

0 25 033

NOAA wind profiler submode information

Code
figure

0	Wind Profiler operating in Submode A
1	Wind Profiler operating in Submode B
2	Reserved
3	Missing value

0 25 034

NOAA wind profiler quality control test results

Bit No.	Meaning (1=true, 0=false)
1	Test A performed and failed
2	Test B performed and failed
3	Test results inconclusive
All 4	Missing value

0 25 036

Atmospherics location method

Code
figure

0	Network of several direction-finders operating on the same individual atmospherics
1	Network of several arrival-time stations operating on the same individual atmospherics
2-5	Reserved
6	Single station range bearing technique
7-14	Reserved
15	Missing value

0 25 040

CO₂ Wind Product Derivation

Code
figure

0	Non-specific mode
1	First guess data
2	Cloud data
3	Average vector data
4	Primary data
5	Guess data
6	Vector data
7	Tracer data;this image
8	Tracer data to next image
9-14	Reserved
15	Missing value

0 25 041

Moving platform direction reporting method

Code
figure

0	Direction originally reported in true degrees
1	Direction originally reported using Code Table 0700, FM13
2	Reserved
3	Missing value

NOTE: Where the original reporting method is as indicated by code figure 1, the following conversion is recommended to obtain a suitable data value corresponding to descriptor 0 01 012:

Reported value	Data value
0	0
1	45
2	90
3	135
4	180
5	225
6	270
7	315
8	360
9	511

0 25 042

Moving platform speed reporting method

Code
figure

0	Speed originally reported in metres per second
1	Speed originally reported using Code Table 4451, FM13
2	Reserved
3	Missing value

NOTE: Where the original reporting method is as indicated by code figure 1, the following conversion is recommended to obtain a suitable data value corresponding to descriptor 0 01 013:

Reported value	Data value
0	0
1	1
2	4
3	7
4	9
5	12
6	14
7	17
8	19
9	21
/	1023

0 25 045

HIRS channel combination

Bit No.	
1-20	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 21	Missing value

0 25 046

MSU channel combination

Bit No.	
1-4	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 5	Missing value

0 25 047

SSU channel combination

Bit No.	
1-3	Beginning with first bit position (high order bit); if bit position is set to 1, then channel is present; if bit position is set to 0, then channel is not present
All 4	Missing value

0 25 048

AMSU-A channel combination

Bit No.	
1-15	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 16	Missing value

0 25 049

AMSU-B channel combination

Bit No.	
1-5	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 6	Missing value

0 25 051

AVHRR channel combination

Bit No.	
1-6	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 7	Missing value

0 25 053

Observation quality

Bit No.	
1	Good
2	Redundant
3	Questionable
4	Bad
5	Experimental
6	Precipitating
7-11	Reserved
All 12	Missing value

0 25 086

Depth correction indicator

Code figure	
0	Depths are not corrected
1	Depths are corrected
2	Reserved
3	Missing value

0 25 093

RASS computation correction

Bit No.	
1	No correction
2	Vertical velocity correction
3-6	Reserved
7	All corrections
All 8	Missing value

0 26 010

Hours included

Bit No.	
1	0100 included
2	0200 included
3	0300 included
4	0400 included
5	0500 included
6	0600 included
7	0700 included
8	0800 included
9	0900 included
10	1000 included
11	1100 included
12	1200 included
13	1300 included
14	1400 included
15	1500 included
16	1600 included
17	1700 included
18	1800 included
19	1900 included
20	2000 included
21	2100 included
22	2200 included
23	2300 included
24	2400 included
25	Unknown mixture of hours
All 26	Missing value

0 29 001

Projection type

Code
figure

0	Gnomonic projection
1	Polar stereographic projection
2	Lambert's conformal conic projection
3	Mercator's projection
4	Scanning Cone (radar)*
5-6	Reserved
7	Missing value

* Projection type 4 indicates a Cartesian grid placed directly on the scanning cone defined by the azimuthal sweep of the radar.

0 29 002

Co-ordinate grid type

Code
figure

0	Cartesian
1	Polar
2	Other
3-6	Reserved
7	Missing value

0 30 031

Picture type

Code figure	
0	PPI
1	Composite
2	CAPPI
3	Vertical section
4	Alphanumeric data
5	Map of subject clutter
6	Map
7	Test picture
8	Comments
9	Map of ground occultation
10	Map of radar beam height
11-13	Reserved
14	Other
15	Missing value

0 30 032

Combination with other data

Bit No.	
1	Map
2	Satellite IR
3	Satellite VIS
4	Satellite WV
5	Satellite multispectral
6	Synoptic observations
7	Forecast parameters
8	Lightning data
9-14	Reserved
15	Other data
All 16	Missing value

0 31 021

Associated field significance

Code figure		
0	Reserved	
1	1-bit indicator of quality	0 = good 1 = suspect or bad
2	2-bit indicator of quality	0 = good 1 = slightly suspect 2 = highly suspect 3 = bad
3-5	Reserved	
6	Quality Control Flag according to GTSP	0 = Unqualified 1 = Correct value (all checks passed) 2 = Probably good but value inconsistent with statistics (differ from climatology) 3 = Probably bad (spike, gradient, ... if other tests passed) 4 = Bad value, Impossible value (out of scale, vertical instability, constant profile) 5 = Value modified during quality control 6-7 = Not used (reserved) 8 = Interpolated value 9 = Missing value
7	Percentage confidence	
8-20	Reserved	
21	1-bit indicator of correction (see Note (2))	0 = original value 1 = substituted/corrected value
22-62	Reserved for local use	
63	Missing value	

Notes

- (1) Associated field significance shall be used initially in conjunction with the quality of observed data.
- (2) The code figure 21 may be used within corrected messages with the corrected/ substituted values identified.
- (3) Further applications may be developed.

0 31 031

Data Present Indicator

Bit No.	Value	Meaning
1	0	Data present
	1	Data not present

0 33 002

Quality Information

Code
figure

0	Data not suspect
1	Data suspect
2	Reserved
3	Quality information not given

0 33 003

Quality Information

Code
figure

0	Data not suspect
1	Data slightly suspect
2	Data highly suspect
3	Data considered unfit for use
4-6	Reserved
7	Quality information not given

0 33 020

Quality control indication of following value

Code
figure

0	Good
1	Inconsistent
2	Doubtful
3	Wrong
4	Not checked
5	Has been changed
6	Reserved
7	Missing value

0 33 021

Quality of following value

Code
figure

0	Within limits
1	Outside limits
2	Reserved
3	Missing value

0 33 022

Quality of buoy satellite transmission

Code
figure

- 0 Good (several identical reports have been received)
- 1 Dubious (no identical reports have been received)
- 2 Reserved
- 3 Missing value

0 33 023

Quality of buoy location

Code
figure

- 0 Reliable (location was made over two satellite passes)
- 1 Latest known (no location over the corresponding pass)
- 2 Dubious (location made over one pass only; a second solution is possible in 5 per cent of the cases)
- 3 Missing value

0 33 024

Station elevation quality mark (for mobile stations)

Code
figure

- 0 Reserved
- 1 Excellent - within 3 meters
- 2 Good - within 10 meters
- 3 Fair - within 20 meters
- 4 Poor - more than 20 meters
- 5 Excellent - within 10 feet
- 6 Good - within 30 feet
- 7 Fair - within 60 feet
- 8 Poor - more than 60 feet
- 9-14 Reserved
- 15 Missing value

0 33 025

ACARS interpolated values

Code
figure

- 0 Time interpolated, latitude and longitude reported
- 1 Time reported, latitude and longitude interpolated
- 2 Time, latitude, and longitude interpolated
- 3 Time, latitude, and longitude reported
- 4-6 Reserved
- 7 Missing value

0 33 026

Moisture quality

Code figure	
0	Normal operations - measurement mode
1	Normal operations - non-measurement mode
2	Small RH
3	Humidity element is wet
4	Humidity element contaminated
5	Heater fail
6	Heater fail and wet/contaminated humidity element
7	At least one of the input parameters used in the calculation of mixing ratio is invalid
8	Numeric error
9	Sensor not installed
10-62	Reserved
63	Missing value

0 33 027

Location quality class (range of radius of 66% confidence)

Code figure	
0	Radius \geq 1500 m
1	500 m \leq Radius $<$ 1500 m
2	250 m \leq Radius $<$ 500 m
3	Radius $<$ 250 m
4-6	Reserved
7	Missing value

0 33 030

Scan line status flags for ATOVS

Bit No.	
1	Do not use scan for product generation
2	Time sequence error detected with this scan
3	Data gap precedes this scan
4	No calibration
5	No earth location
6	First good time following a clock update
7	Instrument status changed with this scan
8-23	Reserved
All 24	Missing value

Notes: If bit is set to 1 then statement is true.

0 33 031

Scan line quality flags for ATOVS

Bit No.	
1	Time field is bad but can probably be inferred from the previous good time
2	Time field is bad and can't be inferred from the previous good time
3	This record starts a sequence that is inconsistent with previous times (i.e. there is a time discontinuity). This may or may not be associated with a spacecraft clock update (see scan line status flags for ATOVS)
4	Start of a sequence that apparently repeats scan times that have been previously accepted
5	Scan line was not calibrated because of bad time
6	Scan line was calibrated using fewer than the preferred number of scan lines because of proximity to start or end of data or to a data gap
7	Scan line was not calibrated because of bad or insufficient PRT data
8	Scan line was calibrated but with marginal PRT data
9	Some uncalibrated channels on this scan
10	Uncalibrated due to instrument mode
11	Questionable calibration because of antenna position error of space view
12	Questionable calibration because of antenna position error of black body
13	Not earth located because of bad time
14	Earth location questionable because of questionable time code (see time problem code bits)
15	Earth location questionable - only marginal agreement with reasonableness check
16	Earth location questionable - fails reasonableness check
17	Earth location questionable because of antenna position check
18	Scan line calibration cold black body
19	Scan line calibration warm black body
20	Scan line calibration space view
21	Earth view
22-23	Reserved
All 24	Missing value

Notes:

- (1) If bit is set to 1 then statement is true.
- (2) Bits 1-4 represent TIME PROBLEM CODE. All bits off implies the scan time is as expected.
- (3) Bits 5-10 represent CALIBRATION PROBLEM CODE. All bits set to zero indicates normal calibration. Where any of bits 5,7,10 are set, secondary calibration coefficients have been used.
- (4) Bits 11-17 represent EARTH LOCATION PROBLEM CODE. All bits set to zero implies the earth location was normal.

0 33 032

Channel quality flags for ATOVS

Bit No.	
1	No good blackbody counts for scan line
2	No good space view counts for this line
3	No good PRTs for this line
4	Some bad blackbody view counts for this line
5	Some bad space view counts for this line
6	Some bad PRT temps on this line
7-23	Reserved (bits set to zero)
All 24	Missing value

Notes: All bits off implies a good calibration

0 33 033

Field of view quality flags for ATOVS

Bit No.	
1	Set if secondary calibration used
2-21	Bit n set to 1 if brightness temperature in channel n-1 is physically unreasonable or has not been calculated due to calibration problems
22	Set if all the channels are missing
23	Suspect
All 24	Missing value

Notes:

- (1) All bits off implies a good calibration
- (2) Bits 2-21 used for HIRS, but only bits 2-16 used for AMSU-A and only bits 2-6 used for AMSU-B

0 33 035

Manual/automatic quality control

Code figure	
0	Automatic quality control passed and not manually checked
1	Automatic quality control passed and manually checked and passed
2	Automatic quality control passed and manually checked and deleted
3	Automatic quality control failed and manually not checked
4	Automatic quality control failed and manually checked and failed
5	Automatic quality control failed and manually checked and re-inserted
6-14	Reserved
15	Missing value

0 33 037

Wind correlation error

Bit No.	
1	U departure from guess
2	V departure from guess
3	U & V departure from guess
4	U acceleration
5	V acceleration
6	U & V acceleration
7	Possible land feature
8	U acceleration and possible land feature
9	V acceleration and possible land feature
10	U & V acceleration and possible land feature
11	Bad wind guess
12	Correlation failure
13	Search box off edge of area
14	Target box off edge of area
15	Pixel brightness out of bounds (noisy line)
16	Target outside of lat/long box
17	Target outside of pressure min/max
18	Autoeditor flagged slow vector
19	Autoeditor flagged vectors
All 20	Missing value

0 33 041

Attribute of following value

Code
figure

- 0 The following value is the true value
- 1 The following value is higher than the true value (the measurement hit the lower limit of the instrument)
- 2 The following value is lower than the true value (the measurement hit the higher limit of the instrument)
- 3 Missing value

Note: This descriptor will be associated with visibility data or height of clouds data to specify if the value is bounded. If the reported data is the true value, the code figure is 0. However, the measurement can hit the limit of the instrument measurement capability. If the reported value is higher than the true value, the code figure is 1, if the reported value is lower than the true value, the code figure is 2.

0 35 000

FM and Regional Code number

Code figure	
000-099	International FM Codes
100-199	RA I Codes
200-299	RA II Codes
300-399	RA III Codes
400-499	RA IV Codes
500-599	RA V Codes
600-699	RA VI Codes
700-799	Antarctic Codes
800-999	Reserved
1000-1022	Not used
1023	Missing value

0 35 001

Time-frame for monitoring

Code figure	
0	Real time
1	Near-real time
2	Non-real time
3	Reserved
4	Reserved
5	Reserved
6	Reserved
7	Missing value

0 35 030

Discrepancies in the availability of expected data

Code figure	
0	No discrepancies
1	Non-compliance with standard and recommended practices and procedures including those of monitoring
2	Catalogues of meteorological bulletins not updated in a timely manner
3	Incorrect routeing directories
4	Lack of flexibility in the routeing arrangements
5	Deficiencies in the operation of GTS centres and circuits
6	Loss of data or delays in relaying data on the GTS
7	Routeing of data different from the routeing provided in the plan
8	Various malpractices
9-14	Reserved
15	Missing value

0 35 031

Qualifier on monitoring results

Code figure	
1	Sufficient and all of acceptable quality
2	Sufficient but partly of acceptable quality
3	Insufficient but all of acceptable quality
4	Insufficient and of unacceptable quality
5	Some messages not complete
6	Suspect or wrongly coded groups could not be interpreted confidently
7	Gross coding errors
8	Transmission sequential order not observed
9	Report completely garbled and thus discarded
10	Deficiencies identified and rectified
11	Deficiencies identified but not rectified
12	Deficiencies not identified
13	Measuring errors
14	Mutual inconsistency
15	Temporal inconsistency
16	Forecast error
17	Bias
18	Improve system of quality control
19	Expand training programmes
20-98	Reserved
99-122	Not used
123	Missing value

0 35 032

Cause of missing data

Code figure	
1	Data groups missing due to radio fading
2	Data groups missing due to outage of centre
3	Data groups missing due to outage of circuit
4	Non-implementation or maintenance of required RBSN density
5	Shortage of qualified staff to man stations
6	Lack of consumables
7	Instrument failure
8	Non-adherence to telecommunication procedures
9	Some observing programmes ceased
10-14	Not used
15	Missing value

0 35 033

Observation and collection deficiency

Code figure	
1	No deficiency
2	Observations not made regularly
3	Observations not made at right time
4	Observations made but not disseminated
5	Observations made and sent to incorrect users
6	Collection not received
7	Collection transmitted late
8	Collection not transmitted
9	Difficulties in HF propagation and selection of suitable frequency
10	Difficulties in maintenance of communication equipment at remote stations
11	No alternative arrangement for routing meteorological observation
12-99	Reserved
100-122	Not used
123	Missing value

0 35 034

Statistical trends for availability of data (during the survey period(s))

Code figure	
1	Slight improvement
2	Significant improvement
3	Most significant improvement
4	Steady
5	Decreasing
6	Efforts required to improve night-time observations
7	Missing value
